U.S. DEPARTMENT OF COMMERCE
National Technical Information Service

PB-257 300

Effluent Limitations Guidelines for Existing Sources and Standards of Performance for New Sources

National Field Investigations Center

Aug 74

PB 257 300

264047

REPRODUCED BY
NATIONAL TECHNICAL
INFORMATION SERVICE
U. S. DEPARTMENT OF COMMERCE
SPRINGFIELD, VA. 22161

BIBLIOGRAPHIC DATA SHEET	1. Report No. EPA/330/9-74/001	2.	3. Recipient's Accession No. PB-257 300
4. Title and Subtitle Effluent Limitations Guidelines for Existing Sources and Standards of Performance for New Sources.			5. Report Date August 1974 6.
7. Author(s)			8. Performing Organization Rept. No.
9. Performing Organization Name and Address National Field Investigations Center Denver, Colorado			10. Project/Task/Work Unit No. 11. Contract/Grant No.
12. Sponsoring Organization Name and Address			13. Type of Report & Period Covered 14.

15. Supplementary Notes

16. Abstracts

An index of limitations for industrial wastes is presented, by industries and by time units, for existing and expected point sources. The effluent guidelines are to be achieved (1) by July 1977 and (2) by July 1983.

17. Key Words and Document Analysis. 17a. Descriptors

*Water pollution abatement	Sugars	Paper products
*Regulations	Guidelines	Wood products
*Industrial wastes	Textile industry	Refineries
Sources	Cements	Metal industry
Effluents	Electroplating	Electric power generation
Contaminants	Chemical industry	Leather
Limits	Plastics industry	Glass industry
Dairies	Cleaning agents	Asbestos
Grains(Food)	Fertilizers	Rubber industry
Canning	Meat	

17b. Identifiers/Open-Ended Terms

*Point sources
Feedlots
Phosphates

17c. COSATI Field/Group 13B

18. Availability Statement National Technical Information Service Springfield, VA 22161	19. Security Class (This Report) UNCLASSIFIED	21. No. of Pages 130
	20. Security Class (This Page) UNCLASSIFIED	22. Price PC$6.00/ MF$2.25

FORM NTIS-35 (REV. 10-73) ENDORSED BY ANSI AND UNESCO. THIS FORM MAY BE REPRODUCED USCOMM-DC 8265-P74

EPA-330/9-74-001

Summary

of

FINAL

Effluent Limitations Guidelines for Existing Sources

and

Standards of Performance for New Sources

for 28 Point Source Categories

Environmental Protection Agency

Office of Enforcement

National Field Investigations Center - Denver

Building 53, Box 25227, Denver Federal Center

Denver, Colorado 80225

August 1974

CONTENTS

	Page
PART 405 - DAIRY PRODUCTS PROCESSING INDUSTRY	1
PART 406 - GRAIN MILLS	10
PART 407 - CANNED AND PRESERVED FRUITS AND VEGETABLE PROCESSING	12
PART 408 - CANNED AND PRESERVED SEAFOOD PROCESSING	14
PART 409 - SUGAR PROCESSING INDUSTRIES	18
PART 410 - TEXTILE INDUSTRY	22
PART 411 - CEMENT MANUFACTURING	29
PART 412 - FEEDLOTS	30
PART 413 - ELECTROPLATING	32
PART 414 - ORGANIC CHEMICALS	34
PART 415 - INORGANIC CHEMICALS	37
PART 416 - PLASTICS AND SYNTHETICS	49
PART 417 - SOAP AND DETERGENT	58
PART 418 - FERTILIZER MANUFACTURING	68
PART 419 - PETROLEUM REFINING	71
PART 420 - IRON AND STEEL MANUFACTURING	83
PART 421 - NONFERROUS METALS	88
PART 422 - PHOSPHATE MANUFACTURING	91

CONTENTS

(Continued)

Page

PART 423 - STEAM ELECTRIC POWER GENERATING EQUIPMENT 93

PART 424 - FERROALLOY MANUFACTURING 98

PART 425 - LEATHER TANNING AND FINISHING 100

PART 426 - GLASS MANUFACTURING 106

PART 427 - ASBESTOS MANUFACTURING 109

PART 428 - RUBBER PROCESSING 111

PART 429 - TIMBER PRODUCTS 113

PART 430 - PULP, PAPER AND PAPERBOARD 116

PART 431 - BUILDERS PAPER AND BOARD 118

PART 432 - MEAT PRODUCTS 119

DEFINITIONS

*BPT - Effluent limitations guidelines to be achieved no later than July 1, 1977 representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

BAT - Effluent limitations guidelines to be achieved no later than July 1, 1983 representing the degree of effluent reduction attainable by application of the best available technology economically available.

New Sources -Effluent reduction to be achieved by New Sources through application of the best available demonstrated control technology, processes, operating methods, or other alternatives.

*In establishing the limitations set forth for BPT, EPA took into account all information it was able to collect, develop and solicit with respect to factors (such as age and size of plant, raw materials, manufacturing processes, products produced, treatment technology available, energy requirements and costs) which can affect the industry subcategorization and effluent levels established. It is, however, possible that data which would affect these limitations have not been available and, as a result, these limitations should be adjusted for certain plants in this industry. An individual discharger or other interested person may submit evidence to the Regional Administrator (or to the State, if the State has the authority to issue NPDES permits) that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the guidelines. On the basis of such evidence or other available information, the Regional Administrator (or the State) will make a written finding that such factors are or are not fundamentally different for that facility compared to those specified in the Development Document. If such fundamentally different factors are found to exist, the Regional Administrator or the State shall establish for the discharger effluent limitations in the NPDES permit either more or less stringent than the limitations established herein, to the extent dictated by such fundamentally different factors. Such limitations must be approved by the Administrator of the Environmental Protection Agency. The Administrator may approve or disapprove such limitations, specify other limitations, or initiate proceedings to revise these regulations.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS	**FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74**					
Subpart A - Receiving Stations Subcategory						
(a) For receiving stations receiving more than 150,000 lb/day of milk equivalent (15,600 lb/day or more of BOD5 input).						
BOD5	0.048 lb/100 lb of BOD5 input	0.019 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input	0.005 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input	0.005 lb/100 lb of BOD5 input
TSS	0.071 lb/100 lb of BOD5 input	0.029 lb/100 lb of BOD5 input	0.013 lb/100 lb of BOD5 input	0.006 lb/100 lb of BOD5 input	0.013 lb/100 lb of BOD5 input	0.006 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For receiving stations receiving 150,000 lb/day or less of milk equivalent (under 15,600 lb/day of BOD5 input).						
BOD5	0.063 lb/100 lb of BOD5 input	0.031 lb/100 lb of BOD5 input	0.015 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input	0.005 lb/100 lb of BOD5 input
TSS	0.094 lb/100 lb of BOD5 input	0.047 lb/100 lb of BOD5 input	0.019 lb/100 lb of BOD5 input	0.009 lb/100 lb of BOD5 input	0.013 lb/100 lb of BOD5 input	0.006 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Fluid Products Subcategory						
(a) For fluid products plants receiving more than 250,000 lb/day of milk equivalent (more than 25,900 lb/day of BOD5 input).						
BOD5	0.338 lb/100 lb of BOD5 input	0.135 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.037 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.037 lb/100 lb of BOD5 input
TSS	0.551 lb/100 lb of BOD5 input	0.203 lb/1000 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.046 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.046 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart B - Fluid Products Subcategory (Continued)						
(b) For fluid products plants receiving 250,000 lb/day or less of milk equivalent (less than 25,900 lb/day of BOD5 input).						
BOD5	0.450 lb/100 lb of BOD5 input	0.225 lb/100 lb of BOD5 input	0.110 lb/100 lb of BOD5 input	0.055 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.037 lb/100 lb of BOD5 input
TSS	0.675 lb/100 lb of BOD5 input	0.338 lb/100 lb of BOD5 input	0.138 lb/100 lb of BOD5 input	0.069 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.046 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart C - Cultured Products Subcategory						
(a) For cultured products plants receiving more than 60,000 lb/day of milk equivalent (more than 6,200 lb/day of BOD5 input).						
BOD5	0.338 lb/100 lb of BOD5 input	0.135 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.037 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.037 lb/100 lb of BOD5 input
TSS	0.506 lb/100 lb of BOD5 input	0.203 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.046 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.046 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For cultured products plants receiving 60,000 lb/day or less of milk equivalent (less than 6,200 lb/day of BOD5 input).						
BOD5	0.450 lb/100 lb of BOD5 input	0.225 lb/100 lb of BOD5 input	0.110 lb/100 lb of BOD5 input	0.055 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.037 lb/100 lb of BOD5 input
TSS	0.675 lb/100 lb of BOD5 input	0.338 lb/100 lb of BOD5 input	0.138 lb/100 lb of BOD5 input	0.069 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.046 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart D - Butter Subcategory						
(a) For plants processing more than 175,000 lb/day of milk equivalent (more than 18,180 lb/day of BOD5 input).						
BOD5	0.138 lb/100 lb of BOD5 input	0.055 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input
TSS	0.206 lb/100 lb of BOD5 input	0.083 lb/100 lb of BOD5 input	.020 lb/100 lb of BOD5 input	.010 lb/100 lb of BOD5 input	0.020 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For plants processing 175,000 lb/day or less of milk equivalent (less than 18,180 lb/day of BOD5 input).						
BOD5	0.183 lb/100 lb of BOD5 input	0.091 lb/100 lb of BOD5 input	0.025 lb/100 lb of BOD5 input	0.013 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input
TSS	0.274 lb/100 lb of BOD5 input	0.137 lb/100 lb of BOD5 input	0.031 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.020 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Cottage Cheese and Cultured Cream Cheese Subcategory						
(a) For plants processing more than 25,000 lb/day of milk equivalent (more than 2,600 lb/day of BOD5 input).						
BOD5	0.670 lb/100 lb of BOD5 input	0.268 lb/100 lb of BOD5 input	0.148 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input	0.148 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input
TSS	1.005 lb/100 lb of BOD5 input	0.402 lb/100 lb of BOD5 input	0.185 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input	0.185 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart E - Cottage Cheese and Cultured Cream Cheese Subcategory (Continued)						
(b) For plants processing 25,000 lb/day or less of milk equivalent (less than 2,600 lb/day of BOD5 input).						
BOD5	0.893 lb/100 lb of BOD5 input	0.446 lb/100 lb of BOD5 input	0.223 lb/100 lb of BOD5 input	0.111 lb/100 lb of BOD5 input	0.148 lb/100 lb of BOD5 input	0.074 lb/100 lb of BOD5 input
TSS	1.339 lb/100 lb of BOD5 input	0.669 lb/100 lb of BOD5 input	0.278 lb/100 lb of BOD5 input	0.139 lb/100 lb of BOD5 input	0.185 lb/100 lb of BOD5 input	0.093 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart F - Natural and Processed Cheese Subcategory						
(a) For plants processing more than 100,000 lb/day of milk equivalent (more than 10,390 lb/day of BOD5 input).						
BOD5	0.073 lb/100 lb of BOD5 input	0.029 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input
TSS	0.109 lb/100 lb of BOD5 input	0.044 lb/100 lb of BOD5 input	0.020 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input	0.020 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For plants processing 100,000 lb/day or less of milk equivalent (less than 10,390 lb/day of BOD5 input).						
BOD5	0.098 lb/100 lb of BOD5 input	0.049 lb/100 lb of BOD5 input	0.025 lb/100 lb of BOD5 input	0.013 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.008 lb/100 lb of BOD5 input
TSS	0.146 lb/100 lb of BOD5 input	0.073 lb/100 lb of BOD5 input	0.031 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.020 lb/100 lb of BOD5 input	0.010 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart G - Fluid Mix for Ice Cream and Other Frozen Desserts Subcategory						
(a) For plants with a dairy products input of more than 85,000 lb/day of milk equivalent (more than 8,830 lb/day of BOD5 input).						
BOD5	0.220 lb/100 lb of BOD5 input	0.088 lb/100 lb of BOD5 input	0.048 lb/100 lb of BOD5 input	0.024 lb/100 lb of BOD5 input	0.048 lb/100 lb of BOD5 input	0.024 lb/100 lb of BOD5 input
TSS	0.254 lb/100 lb of BOD5 input	0.132 lb/100 lb of BOD5 input	0.060 lb/100 lb of BOD5 input	0.030 lb/100 lb of BOD5 input	0.060 lb/100 lb of BOD5 input	0.030 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For plants with a dairy products input of 85,000 lb/day or less of milk equivalent (less than 8,830 lb/day of BOD5 input).						
BOD5	0.293 lb/100 lb of BOD5 input	0.146 lb/100 lb of BOD5 input	0.073 lb/100 lb of BOD5 input	0.036 lb/100 lb of BOD5 input	0.048 lb/100 lb of BOD5 input	0.024 lb/100 lb of BOD5 input
TSS	0.439 lb/100 lb of BOD5 input	0.219 lb/100 lb of BOD5 input	0.091 lb/100 lb of BOD5 input	0.45 lb/100 lb of BOD5 input	0.060 lb/100 lb of BOD5 input	0.030 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart H - Ice Cream, Frozen Desserts, Novelties and Other Dairy Desserts Subcategory						
(a) For plants with a dairy products input of more than 85,000 lb/day of milk equivalent (more than 8,830 lb/day of BOD5 input).						
BOD5	0.460 lb/100 lb of BOD5 input	0.184 lb/100 lb of BOD5 input	0.094 lb/100 lb of BOD5 input	0.047 lb/100 lb of BOD5 input	0.094 lb/100 lb of BOD5 input	0.047 lb/100 lb of BOD5 input
TSS	.690 lb/100 lb of BOD5 input	.276 lb/100 lb of BOD5 input	.118 lb/100 lb of BOD5 input	.059 lb/100 lb of BOD5 input	.118 lb/100 lb of BOD5 input	.059 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart H - Ice Cream, Frozen Desserts, Novelties and Other Dairy Desserts Subcategory (Continued)						
(b) For plants with a dairy products input of 85,000 lb/day or less of milk equivalent (less than 8,830 lb/day of BOD5 input).						
BOD5	0.613 lb/100 lb of BOD5 input	0.306 lb/100 lb of BOD5 input	0.140 lb/100 lb of BOD5 input	0.070 lb/100 lb of BOD5 input	0.094 lb/100 lb of BOD5 input	0.047 lb/100 lb of BOD5 input
TSS	.919 lb/100 lb of BOD5 input	.459 lb/100 lb of BOD5 input	.175 lb/100 lb of BOD5 input	.088 lb/100 lb of BOD5 input	.118 lb/100 lb of BOD5 input	.059 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart I - Condensed Milk Subcategory						
(a) For plants condensing more than 100,000 lb/day of milk equivalent (more than 10,390 lb/day of BOD5 input).						
BOD5	0.345 lb/100 lb of BOD5 input	0.138 lb/100 lb of BOD5 input	0.076 lb/100 lb of BOD5 input	0.038 lb/100 lb of BOD5 input	0.076 lb/100 lb of BOD5 input	0.038 lb/100 lb of BOD5 input
TSS	.518 lb/100 lb of BOD5 input	.207 lb/100 lb of BOD5 input	.095 lb/100 lb of BOD5 input	.048 lb/100 lb of BOD5 input	.095 lb/100 lb of BOD5 input	.048 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For plants condensing 100,000 lb/day or less of milk equivalent (less than 10,390 lb/day of BOD5 input).						
BOD5	0.460 lb/100 lb of BOD5 input	0.184 lb/100 lb of BOD5 input	0.115 lb/100 lb of BOD5 input	0.058 lb/100 lb of BOD5 input	0.076 lb/100 lb of BOD5 input	0.038 lb/100 lb of BOD5 input
TSS	.690 lb/100 lb of BOD5 input	.276 lb/100 lb of BOD5 input	.144 lb/100 lb of BOD5 input	.072 lb/100 lb of BOD5 input	.095 lb/100 lb of BOD5 input	.048 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 405 - DAIRY PRODUCTS (Continued) FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74

Subpart I - Condensed Milk Subcategory (Continued)

(c) For plants in the size range covered by (b) once-through barometric condenser water may be discharged untreated if the composite net entrainment is below 15 mg/l of BOD5 for any one day and below 10 mg/l of BOD5 as the average for thirty consecutive days.

Subpart J - Dry Milk Subcategory

(a) For milk drying plants with an input equivalent to more than 145,000 lb/day of milk equivalent (more than 15,070 lb/day of BOD5 input).

BOD5	0.163 lb/100 lb of BOD5 input	0.065 lb/100 lb of BOD5 input	0.036 lb/100 lb of BOD5 input	0.018 lb/100 lb of BOD5 input	0.036 lb/100 lb of BOD5 input	0.018 lb/100 lb of BOD5 input
TSS	.244 lb/100 lb of BOD5 input	.098 lb/100 lb of BOD5 input	.045 lb/100 lb of BOD5 input	.023 lb/100 lb of BOD5 input	.045 lb/100 lb of BOD5 input	.023 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

(b) For milk drying plants with an input equivalent to 145,000 lb/day or less of milk equivalent (less than 15,070 lb/day of BOD5 input).

BOD5	0.218 lb/100 lb of BOD5 input	0.109 lb/100 lb of BOD5 input	0.055 lb/100 lb of BOD5 input	0.028 lb/100 lb of BOD5 input	0.036 lb/100 lb of BOD5 input	0.018 lb/100 lb of BOD5 input
TSS	.328 lb/100 lb of BOD5 input	.164 lb/100 lb of BOD5 input	.069 lb/100 lb of BOD5 input	.034 lb/100 lb of BOD5 input	.045 lb/100 lb of BOD5 input	.023 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart K - Condensed Whey Subcategory						
(a) For whey condensing plants with over 300,000 lb/day of fluid raw whey input (over 20,700 lb/day of solids or 14,160 lb/day of BOD5 input).						
BOD5	0.100 lb/100 lb of BOD5 input	0.040 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input
TSS	.150 lb/100 lb of BOD5 input	.060 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For whey condensing plants with 300,000 lb/day or less of raw fluid whey input (less than 20,700 lb/day of solids or 14,160 lb/day of BOD5 input).						
BOD5	0.130 lb/100 lb of BOD5 input	0.065 lb/100 lb of BOD5 input	0.033 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input
TSS	.195 lb/100 lb of BOD5 input	.098 lb/100 lb of BOD5 input	.041 lb/100 lb of BOD5 input	.020 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c)	For plants in the size range covered in (b) once-through barometric condenser water may be discharged untreated if the composite net entrainment is below 15 mg/l of BOD5 for any one day and below 10 mg/l of BOD5 as the average for thirty consecutive days.					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart L - Dry Whey Subcategory						
(a) For whey drying plants with an input equivalent to more than 57,000 lb/day of 40 percent solids whey (22,800 lb/day of solids or 15,620 lb/day of BOD5 input).						
BOD5	0.100 lb/100 lb of BOD5 input	0.040 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input
TSS	.150 lb/100 lb of BOD5 input	.060 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For whey drying plants with an input equivalent to 57,000 lb/day or less of 40 percent solids whey (under 22,800 lb/day solids or 15,620 lb/day of BOD5 input).						
BOD5	0.130 lb/100 lb of BOD5 input	0.065 lb/100 lb of BOD5 input	0.033 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input
TSS	.195 lb/100 lb of BOD5 input	.098 lb/100 lb of BOD5 input	.041 lb/100 lb of BOD5 input	.020 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 405 - DAIRY PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 5/28/74, EFFECTIVE 5/28/74					
Subpart L - Dry Whey Subcategory						
(a) For whey drying plants with an input equivalent to more than 57,000 lb/day of 40 percent solids whey (22,800 lb/day of solids or 15,620 lb/day of BOD5 input).						
BOD5	0.100 lb/100 lb of BOD5 input	0.040 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input
TSS	.150 lb/100 lb of BOD5 input	.060 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For whey drying plants with an input equivalent to 57,000 lb/day or less of 40 percent solids whey (under 22,800 lb/day solids or 15,620 lb/day of BOD5 input).						
BOD5	0.130 lb/100 lb of BOD5 input	0.065 lb/100 lb of BOD5 input	0.033 lb/100 lb of BOD5 input	0.016 lb/100 lb of BOD5 input	0.022 lb/100 lb of BOD5 input	0.011 lb/100 lb of BOD5 input
TSS	.195 lb/100 lb of BOD5 input	.098 lb/100 lb of BOD5 input	.041 lb/100 lb of BOD5 input	.020 lb/100 lb of BOD5 input	.028 lb/100 lb of BOD5 input	.014 lb/100 lb of BOD5 input
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 406 - GRAIN MILLS	**FINAL REGULATIONS, PUBLISHED 3/20/74, EFFECTIVE 5/20/74**					
Subpart A - Corn Wet Milling Subcategory						
BOD5	150 lb/1000 std bu corn	50 lb/1000 std bu corn	60 lb/1000 std bu corn	20 lb/1000 std bu corn	60 lb/1000 std bu corn	20 lb/1000 std bu corn
TSS	150 lb/1000 std bu corn	50 lb/1000 std bu corn	30 lb/1000 std bu corn	10 lb/1000 std bu corn	30 lb/1000 std bu corn	10 lb/1000 std bu corn
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Corn Dry Milling Subcategory						
BOD5	12.0 lb/1000 std bu corn	4.0 lb/1000 std bu corn	6.0 lb/1000 std bu corn	2.0 lb/1000 std bu corn	6.0 lb/1000 std bu corn	2.0 lb/1000 std bu corn
TSS	10.5 lb/1000 std bu corn	3.5 lb/1000 std bu corn	3.0 lb/1000 std bu corn	1.0 lb/1000 std bu corn	3.0 lb/1000 std bu corn	1.0 lb/1000 std bu corn
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart C - Normal Wheat Flour Milling Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart D - Bulgur Wheat Flour Milling Subcategory						
BOD5	1.50 lb/1000 std bu corn	0.50 lb/1000 std bu corn	0.90 lb/1000 std bu corn	0.30 lb/1000 std bu corn	0.90 lb/1000 std bu corn	0.30 lb/1000 std bu corn
TSS	1.50 lb/1000 std bu corn	.50 lb/1000 std bu corn	.60 lb/1000 std bu corn	.20 lb/1000 std bu corn	.60 lb/1000 std bu corn	.20 lb/1000 std bu corn
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Normal Rice Milling Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 406 - GRAIN MILLS (Continued)	FINAL REGULATIONS, PUBLISHED 3/20/74, EFFECTIVE 5/20/74					
Subpart F - Parboiled Rice Processing Subcategory						
BOD5	0.042 lb/100 wt rice	0.014 lb/100 wt rice	0.021 lb/100 wt rice	0.007 lb/100 wt rice	0.021 lb/100 wt rice	0.007 lb/100 wt rice
TSS	.024 lb/100 wt rice	.008 lb/100 wt rice	.009 lb/100 wt rice	.003 lb/100 wt rice	.009 lb/100 wt rice	.003 lb/100 wtrice
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 407 - CANNED AND PRESERVED FRUITS AND VEGETABLES						
			FINAL REGULATIONS, PUBLISHED 3/21/74, EFFECTIVE 5/20/74			
			(All references to lb/1000 lb are to 1000 lb of raw material)			
Subpart A - Apple Juice Subcategory						
BOD5	0.60 lb/1000 lb	0.30 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
TSS	.80 lb/1000 lb	.40 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Fecal Coliform			Max. at any time 400 counts/100 ml		Max. at any time 400 counts/100 ml	
Subpart B - Apple Products Subcategory						
BOD5	1.10 lb/1000 lb	0.55 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
TSS	1.40 lb/1000 lb	.70 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Fecal Coliform			Max. at any time 400 counts/100 ml		Max. at any time 400 counts/100 ml	
Subpart C - Citrus Products Subcategory						
BOD5	0.80 lb/1000 lb	0.40 lb/1000 lb	0.14 lb/1000 lb	0.07 lb/1000 lb	0.14 lb/1000 lb	0.07 lb/1000 lb
TSS	1.70 lb/1000 lb	0.85 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Fecal Coliform			Max. at any time 400 counts/100 ml		Max. at any time 400 counts/100 ml	
Subpart D - Frozen Potato Products Subcategory						
BOD5	2.80 lb/1000 lb	1.40 lb/1000 lb	0.34 lb/1000 lb	0.17 lb/1000 lb	0.34 lb/1000 lb	0.17 lb/1000 lb
TSS	2.80 lb/1000 lb	1.40 lb/1000 lb	1.10 lb/1000 lb	.55 lb/1000 lb	1.10 lb/1000 lb	.55 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Fecal Coliform			Max. at any time 400 counts/100 ml		Max. at any time 400 counts/100 ml	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 407 - CANNED AND PRESERVED FRUITS AND VEGETABLES			FINAL REGULATIONS, PUBLISHED 3/21/74, EFFECTIVE 5/20/74			
Subpart E - Dehydrated Potato Products Subcategory						
BOD5	2.40 lb/1000 lb	1.20 lb/1000 lb	0.34 lb/1000 lb	0.17 lb/1000 lb	0.34 lb/1000 lb	0.17 lb/1000 lb
TSS	2.80 lb/1000 lb	1.40 lb/1000 lb	1.10 lb/1000 lb	.55 lb/1000 lb	1.10 lb/1000 lb	.55 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Fecal Coliform			Max. at any time 400 counts/100 ml		Max. at any time 400 counts/100 ml	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 408 - CANNED AND PRESERVED SEAFOOD	FINAL REGULATIONS, PUBLISHED 6/26/74, EFFECTIVE 6/26/74 (All references to lb/1000 lb are to 1000 lb of seafood)					
Subpart A - Farm Raised Catfish Processing Subcategory						
BOD5			4.6 lb/1000 lb	2.3 lb/1000 lb	4.6 lb/1000 lb	2.3 lb/1000 lb
TSS	28 lb/1000 lb	9.2 lb/1000 lb	11 lb/1000 lb	5.7 lb/1000 lb	11 lb/1000 lb	5.7 lb/1000 lb
Oil & Grease	10 lb/1000 lb	3.4 lb/1000 lb	0.90 lb/1000 lb	0.45 lb/1000 lb	0.90 lb/1000 lb	0.45 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Conventional Blue Crab Processing Subcategory						
BOD5			0.30 lb/1000 lb	0.15 lb/1000 lb	0.30 lb/1000 lb	0.15 lb/1000 lb
TSS	2.2 lb/1000 lb	0.74 lb/1000 lb	0.90 lb/1000 lb	0.45 lb/1000 lb	0.90 lb/1000 lb	0.45 lb/1000 lb
Oil & Grease	0.60 lb/1000 lb	0.20 lb/1000 lb	0.13 lb/1000 lb	0.065 lb/1000 lb	0.13 lb/1000 lb	0.065 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart C - Mechanized Blue Crab Processing Subcategory						
BOD5			5.0 lb/1000 lb	2.5 lb/1000 lb	5.0 lb/1000 lb	2.5 lb/1000 lb
TSS	36 lb/1000 lb	12.0 lb/1000 lb	13 lb/1000 lb	6.3 lb/1000 lb	13 lb/1000 lb	6.3 lb/1000 lb
Oil & Grease	13 lb/1000 lb	4.2 lb/1000 lb	2.6 lb/1000 lb	1.3 lb/1000 lb	2.6 lb/1000 lb	1.3 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 408 - CANNED AND PRESERVED SEAFOOD (Continued)			FINAL REGULATIONS, PUBLISHED 6/26/74, EFFECTIVE 6/26/74			
Subpart D - Non-Remote Alaskan Crab Meat Processing Subcategory						
BOD5			5.0 lb/1000 lb	2.0 lb/1000 lb		
TSS	19 lb/1000 lb	6.2 lb/1000 lb	1.3 lb/1000 lb	0.53 lb/1000 lb	16 lb/1000 lb	5.3 lb/1000 lb
Oil & Grease	1.8 lb/1000 lb	0.01 lb/1000 lb	0.21 lb/1000 lb	0.082 lb/1000 lb	1.6 lb/1000 lb	0.52 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Remote Alaskan Crab Meat Processing Subcategory						
TSS	No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.		16 lb/1000 lb	5.3 lb/1000 lb	16 lb/1000 lb	5.3 lb/1000 lb
Oil & Grease			1.6 lb/1000 lb	0.52 lb/1000 lb	1.6 lb/1000 lb	0.52 lb/1000 lb
pH			6.0 - 9.0		6.0 - 9.0	
Subpart F - Non-Remote Alaskan Whole Crab and Crab Section Processing Subcategory						
BOD5			3.3 lb/1000 lb	1.3 lb/1000 lb		
TSS	12 lb/1000 lb	3.9 lb/1000 lb	0.83 lb/1000 lb	0.33 lb/1000 lb	9.9 lb/1000 lb	3.3 lb/1000 lb
Oil & Grease	1.3 lb/1000 lb	0.42 lb/1000 lb	0.12 lb/1000 lb	0.048 lb/1000 lb	1.1 lb/1000 lb	0.36 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart G - Remote Alaskan Whole Crab and Crab Section Processing Subcategory						
TSS	No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.		9.9 lb/1000 lb	3.3 lb/1000 lb	9.9 lb/1000 lb	3.3 lb/1000 lb
Oil & Grease			1.1 lb/1000 lb	0.36 lb/1000 lb	1.1 lb/1000 lb	0.36 lb/1000 lb
pH			6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 408 - CANNED AND PRESERVED SEAFOOD (Continued)			FINAL REGULATIONS, PUBLISHED 6/26/74, EFFECTIVE 6/26/74			
Subpart H - Dungeness and Tanner Crab Processing in the Contiguous States Subcategory						
BOD5			4.3 lb/1000 lb	1.7 lb/1000 lb	10 lb/1000 lb	4.1 lb/1000 lb
TSS	8.1 lb/1000 lb	2.7 lb/1000 lb	0.58 lb/1000 lb	0.23 lb/1000 lb	1.7 lb/1000 lb	0.69 lb/1000 lb
Oil & Grease	1.8 lb/1000 lb	0.61 lb/1000 lb	0.18 lb/1000 lb	0.07 lb/1000 lb	0.25 lb/1000 lb	0.10 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart I - Non-Remote Alaskan Shrimp Processing Subcategory						
BOD5			70 lb/1000 lb	28 lb/1000 lb		
TSS	320 lb/1000 lb	210 lb/1000 lb	45 lb/1000 lb	18 lb/1000 lb	270 lb/1000 lb	180 lb/1000 lb
Oil & Grease	51 lb/1000 lb	17 lb/1000 lb	3.8 lb/1000 lb	1.5 lb/1000 lb	45 lb/1000 lb	15 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart J - Remote Alaskan Shrimp Processing Subcategory						
TSS	No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.		270 lb/1000 lb	180 lb/1000 lb	270 lb/1000 lb	180 lb/1000 lb
Oil & Grease			45 lb/1000 lb	15 lb/1000 lb	45 lb/1000 lb	15 lb/1000 lb
pH			6.0 - 9.0		6.0 - 9.0	
Subpart K - Northern Shrimp Processing in the Contiguous States Subcategory						
BOD5			68 lb/1000 lb	27.0 lb/1000 lb	155 lb/1000 lb	62 lb/1000 lb
TSS	160 lb/1000 lb	54 lb/1000 lb	12 lb/1000 lb	4.9 lb/1000 lb	38 lb/1000 lb	15 lb/1000 lb
Oil & Grease	126 lb/1000 lb	42 lb/1000 lb	9.5 lb/1000 lb	3.8 lb/1000 lb	14 lb/1000 lb	5.7 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 408 - CANNED AND PRESERVED SEAFOOD (Continued)			FINAL REGULATIONS, PUBLISHED 6/26/74, EFFECTIVE 6/26/74			
Subpart L - Southern Non-Breaded Shrimp Processing in the Contiguous States Subcategory						
BOD5			25 lb/1000 lb	10 lb/1000 lb	63 lb/1000 lb	25 lb/1000 lb
TSS	110 lb/1000 lb	38 lb/1000 lb	8.5 lb/1000 lb	3.4 lb/1000 lb	25 lb/1000 lb	10 lb/1000 lb
Oil & Grease	36 lb/1000 lb	12 lb/1000 lb	2.8 lb/1000 lb	1.1 lb/1000 lb	4.0 lb/1000 lb	1.6 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart M - Breaded Shrimp Processing in the Contiguous States Subcategory						
BOD5			43 lb/1000 lb	17.0 lb/1000 lb	100 lb/1000 lb	40 lb/1000 lb
TSS	280 lb/1000 lb	93 lb/1000 lb	19 lb/1000 lb	7.4 lb/1000 lb	55 lb/1000 lb	22 lb/1000 lb
Oil & Grease	36 lb/1000 lb	12 lb/1000 lb	2.5 lb/1000 lb	1.0 lb/1000 lb	3.8 lb/1000 lb	1.5 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart N - Tuna Processing Subcategory						
BOD5	23 lb/1000 lb	9.0 lb/1000 lb	2.2 lb/1000 lb	0.62 lb/1000 lb	20 lb/1000 lb	8.1 lb/1000 lb
TSS	8.3 lb/1000 lb	3.3 lb/1000 lb	2.2 lb/1000 lb	0.62 lb/1000 lb	7.5 lb/1000 lb	3.0 lb/1000 lb
Oil & Grease	2.1 lb/1000 lb	0.84 lb/1000 lb	0.27 lb/1000 lb	0.077 lb/1000 lb	1.9 lb/1000 lb	0.76 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 409 - SUGAR PROCESSING INDUSTRIES	FINAL REGULATIONS PUBLISHED 1/31/74, EFFECTIVE 4/1/74 (All references to lb/1000 lb are to 1000 lb of product)					
Subpart A - Beet Sugar Processing Subcategory						
	(a) The following limitations establish the maximum permissible discharge of process waste water pollutants when the process waste water discharge results from barometric condensing operations only:		(a) Sugar beet processing capacity of the point source does not exceed 2300 tons/day of beets sliced and/or the soil filtration rate in the vicinity of the point source is less than or equal to 1/16 in./day; provided however, that a discharge by a point source may be made in accordance with the limitations set forth in either (a)(1) exclusively, or (a)(2) of this section exclusively. (1) The following limitations establish the maximum permissible discharge of process waste water pollutants when the process waste water discharge results from barometric condensing operations only:		There shall be no discharge of process waste water pollutants to navigable waters.	
BOD5	3.3 lb/1000 lb	2.2 lb/1000 lb	2.0 lb/1000 lb	1.3 lb/1000 lb		
pH	6.0 - 9.0		6.0 - 9.0			
Temperature	Not to exceed temp. of cooled water acceptable for return to the heat producing process and in no event greater than 90°F.		Not to exceed the temp. of cooled water acceptable for return to the heat producing process and in no event greater than 90°F.			

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 409 - SUGAR PROCESSING INDUSTRIES (Continued) FINAL REGULATIONS PUBLISHED 1/31/74, EFFECTIVE 4/1/74

Subpart A - Beet Sugar Processing Subcategory (Continued)

	(b) The following limitations establish the maximum permissible discharge of process waste water pollutants when the process waste water discharge results, in whole or in part, from barometric condensing operations and any other beet sugar processing operation:		(2) The following limitations establish the maximum permissible discharge of process waste water pollutants when the process waste water discharge results, in whole or in part, from barometric condensing operations and any other beet sugar processing operation:	
BOD5	3.3 lb/1000 lb	2.2 lb/1000 lb	2.0 lb/1000 lb	1.3 lb/1000 lb
TSS	3.3 lb/1000 lb	2.2 lb/1000 lb	2.0 lb/1000 lb	1.3 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0	
Fecal Coliform	Not to exceed MPN of 400/100 ml at any time		Not to exceed MPN of 400/100 ml at any time	
Temperature	Not to exceed 90°F		Not to exceed 90°F	

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this regulation, which may be discharged by a point source in all instances not specified under the provisions of (a) above; there shall be no discharge of process waste water pollutants to navigable waters.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 409 - SUGAR PROCESSING CATEGORY	FINAL REGULATIONS, PUBLISHED 3/20/74, EFFECTIVE 5/20/74					
Subpart B - Crystalline Cane Sugar Refining Subcategory						
	(1) Any crystalline cane sugar refinery discharging both barometric condenser cooling water and other process waters shall meet the following limitations. The BOD5 limitation is determined by the addition of the net BOD5 attributed to the barometric condenser cooling water to that amount of BOD5 attributed to the treated process water. The TSS limitation is that amount of TSS attributed to the treated process water. Where the barometric condenser cooling water and process water streams are mixed and impossible to measure separately prior to discharge, the values should be considered net.					
BOD5	2.38 lb/ton of melt	0.86 lb/ton of melt	0.36 lb/ton of melt	0.18 lb/ton of melt	0.36 lb/ton of melt	0.18 lb/ton of melt
TSS	.54 lb/ton of melt	.18 lb/ton of melt	.21 lb/ton of melt	.07 lb/ton of melt	.21 lb/ton of melt	.07 lb/ton of melt
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(2) Any crystalline cane sugar refinery discharging barometric condenser cooling water only should be required to achieve the following net limitations:					
BOD5	2.04 lb/ton of melt	0.68 lb/ton of melt				

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 409 - SUGAR PROCESSING CATEGORY	FINAL REGULATIONS, PUBLISHED 3/20/74, EFFECTIVE 5/20/74					
Subpart C - Liquid Cane Sugar Refining Subcategory						
	(1) Any liquid cane sugar refinery discharging both barometric condenser cooling water and other process waters shall meet the following limitations. The BOD5 limitation is determined by the addition of the net BOD5 attributed to the barometric condenser cooling water to that amount of BOD5 attributed to the treated process water. The TSS limitation is that amount of TSS attributed to the treated process water. Where the barometric condenser cooling water and process water streams are mixed and impossible to measure separately prior to discharge, the values should be considered net.					
BOD5	1.56 lb/ton of melt	0.63 lb/ton of melt	0.60 lb/ton of melt	0.30 lb/ton of melt	0.60 lb/ton of melt	0.30 lb/ton of melt
TSS	.99 lb/ton of melt	.33 lb/ton of melt	.18 lb/ton of melt	.06 lb/ton of melt	.18 lb/ton of melt	.06 lb/ton of melt
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(2) Any liquid cane sugar refinery discharging barometric condenser cooling water only shall meet the following net limitations:					
BOD5	0.90 lb/ton of melt	0.30 lb/ton of melt				

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 410 - TEXTILE INDUSTRY FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74 (All references to lb/1000 lb are to 1000 lb of product)

Subpart A - Wool Scouring Subcategory

	(a)					
BOD5	10.6 lb/1000 lb	5.3 lb/1000 lb	4.8 lb/1000 lb	2.4 lb/1000 lb	10.6 lb/1000 lb	5.3 lb/1000 lb
TSS	32.2 lb/1000 lb	16.1 lb/1000 lb	4.0 lb/1000 lb	2.0 lb/1000 lb	10.6 lb/1000 lb	5.3 lb/1000 lb
COD	138.0 lb/1000 lb	69.0 lb/1000 lb	36.0 lb/1000 lb	18.0 lb/1000 lb	138.0 lb/1000 lb	69.0 lb/1000 lb
Oil & Grease	7.2 lb/1000 lb	3.6 lb/1000 lb	2.0 lb/1000 lb	1.0 lb/1000 lb	7.2 lb/1000 lb	3.6 lb/1000 lb
Total Chromium	0.10 lb/1000 lb	0.05 lb/1000 lb	0.05 lb/1000 lb	0.025 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
Phenol	0.10 lb/1000 lb	0.05 lb/1000 lb	0.05 lb/1000 lb	0.025 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
Sulfide	0.20 lb/1000 lb	0.10 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
Color			Shall not exceed 600 APHA units.			
Fecal Coliform			MPN shall not exceed 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

(b) Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that scours wool through "commission scouring" as defined.

(b) Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that scours wool through "commission scouring" as defined.

(b) Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that scours wool through "commission scouring" as defined.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 410 - TEXTILE INDUSTRY (Continued)	FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74					
Subpart B - Wool Finishing Subcategory						
	(a)					
BOD5	22.4 lb/1000 lb	11.2 lb/1000 lb	9.2 lb/1000 lb	4.6 lb/1000 lb	22.4 lb/1000 lb	11.2 lb/1000 lb
TSS	35.2 lb/1000 lb	17.6 lb/1000 lb	5.0 lb/1000	2.5 lb/1000 lb	22.4 lb/1000 lb	11.2 lb/1000 lb
COD	163.0 lb/1000 lb	81.5 lb/1000 lb	54.2 lb/1000 lb	27.1 lb/1000 lb	163.0 lb/1000 lb	81.5 lb/1000 lb
Total Chromium	0.14 lb/1000 lb	0.07 lb/1000 lb	0.05 lb/1000 lb	0.025 lb/1000 lb	0.14 lb/1000 lb	0.07 lb/1000 lb
Phenol	0.14 lb/1000 lb	0.07 lb/1000 lb	0.05 lb/1000 lb	0.025 lb/1000 lb	0.14 lb/1000 lb	0.07 lb/1000 lb
Sulfide	0.28 lb/1000 lb	0.14 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.28 lb/1000 lb	0.14 lb/1000 lb
Color			Shall not exceed 600 APHA units.			
Fecal Coliform			MPN shall not exceed 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(b)		(b)		(b)	
	Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that finishes wool or blended wool fabrics through "commission finishing" as defined.		Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that finishes wool or blended wool fabrics through "commission finishing" as defined.		Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that finishes wool or blended wool fabrics through "commission finishing" as defined.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 410 - TEXTILE INDUSTRY (Continued)			FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74			
Subpart C - Dry Processing Subcategory						
BOD5	1.4 lb/1000 lb	0.7 lb/1000 lb	0.4 lb/1000 lb	0.2 lb/1000 lb	1.4 lb/1000 lb	0.7 lb/1000 lb
TSS	1.4 lb/1000 lb	0.7 lb/1000 lb	0.4 lb/1000 lb	0.2 lb/1000 lb	1.4 lb/1000 lb	0.7 lb/1000 lb
COD	2.8 lb/1000 lb	1.4 lb/1000 lb	0.8 lb/1000 lb	0.4 lb/1000 lb	2.8 lb/1000 lb	2.4 lb/1000 lb
Fecal Coliform	MPN shall not exceed 400 counts per 100 ml.		MPN shall not exceed 400 counts per 100 ml.		MPN shall not exceed 400 counts per 100 ml	
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart D - Woven Fabric Finishing Subcategory						
(a) Finishing of woven fabrics through simple or complex manufacturing operations employing a natural fiber, a synthetic fiber or a natural and synthetic fiber blend, except as provided in (e) of this section:						
BOD5	6.6 lb/1000 lb	3.3 lb/1000 lb	4.4 lb/1000 lb	2.2 lb/1000 lb	6.6 lb/1000 lb	3.3 lb/1000 lb
TSS	17.8 lb/1000 lb	8.9 lb/1000 lb	3.0 lb/1000 lb	1.5 lb/1000 lb	6.6 lb/1000 lb	3.3 lb/1000 lb
COD	60.0 lb/1000 lb	30.0 lb/1000 lb	20.0 lb/1000 lb	10.0 lb/1000 lb	60.0 lb/1000 lb	30.0 lb/1000 lb
Total Chromium	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
Phenol	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
Sulfide	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
Color			Shall not exceed 300 APHA units			
Fecal Coliform			MPN shall not exceed 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 410 - TEXTILE INDUSTRY (Continued)	FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74					
Subpart D - Woven Fabric Finishing Subcategory (Continued)						
(b) Finishing of woven fabrics through simple manufacturing operations employing a synthetic fiber or complex manufacturing operations employing a natural fiber, except as provided in (e) of this section and in addition to the discharge allowed by (a) of this section:						
COD	20 lb/1000 lb	10 lb/1000 lb	6.6 lb/1000 lb	3.3 lb/1000 lb	20 lb/1000 lb	10 lb/1000 lb
(c) Finishing of woven fabrics through simple manufacturing operations employing a natural and synthetic fiber blend or through complex manufacturing operations employing a synthetic fiber, except as provided in (e) of this section and in addition to the discharge allowed by (a) of this section:						
COD	40 lb/1000 lb	20 lb/1000 lb	13.4 lb/1000 lb	6.7 lb/1000 lb	40 lb/1000 lb	20 lb/1000 lb
(d) Finishing of woven fabrics through complex manufacturing operations employing a natural and synthetic fiber blend, except as provided in (e) of this section and in addition to the discharge allowed by (a) of this section:						
COD	60 lb/1000 lb	30 lb/1000 lb	20 lb/1000 lb	10 lb/1000 lb	60 lb/1000 lb	30 lb/1000 lb
(e) Additional allocations equal to the effluent limitations (except pH) established in (a), (b), (c) and (d) of this section are allowed any point source subject to such effluent limitations that finishes woven fabrics through "commission finishing" as defined.						
Subpart E - Knit Fabric Finishing Subcategory						
(a) Finishing of knit fabrics through simple or complex manufacturing operations employing a synthetic fiber or a natural and synthetic fiber blend, except as provided in (d) of this section:						
BOD5	5.0 lb/1000 lb	2.5 lb/1000 lb	3.4 lb/1000 lb	1.7 lb/1000 lb	5.0 lb/1000 lb	2.5 lb/1000 lb
TSS	21.6 lb/1000 lb	10.9 lb/1000 lb	3.4 lb/1000 lb	1.7 lb/1000 lb	5.0 lb/1000 lb	2.5 lb/1000 lb
COD	60.0 lb/1000 lb	30.0 lb/1000 lb	20.0 lb/1000 lb	10.0 lb/1000 lb	60.0 lb/1000 lb	30.0 lb/1000 lb
Total Chromium	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
Phenol	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
Sulfide	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 410 - TEXTILE INDUSTRY (Continued)	FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74					
Subpart E - Knit Fabric Finishing Subcategory (Continued)						
(a) Finishing of knit fabrics through simple or complex manufacturing operations employing a synthetic fiber or a natural and synthetic fiber blend, except as provided in (d) of this section: (continued)						
Color			Shall not exceed 300 APHA units.			
Fecal Coliform			MPN shall not exceed 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Finishing of knit fabrics through simple manufacturing operations employing a natural and synthetic fiber blend or through complex manufacturing operations employing a synthetic fiber, except as provided in (d) of this section and in addition to the discharge allowed by (a) of this section:						
COD	20 lb/1000 lb	10 lb/1000 lb	6.6 lb/1000 lb	3.3 lb/1000 lb	20 lb/1000 lb	10 lb/1000 lb
(c) Finishing of knit fabrics through complex manufacturing operations employing a natural and synthetic fiber blend, except as provided in (d) of this section and in addition to the discharge allowed by (a) of this section:						
COD	40 lb/1000 lb	20 lb/1000 lb	13.4 lb/1000 lb	6.7 lb/1000 lb	40 lb/1000 lb	20 lb/1000 lb
(d) Additional allocations equal to the effluent limitations(except pH) established in (a), (b), and (c) of this section are allowed any point source subject to such effluent limitations that finish knit fabrics through "commission finishing" as defined.						
Subpart F - Carpet Mills Subcategory						
(a) Manufacture of carpets through simple or complex manufacturing operations:						
BOD5	7.8 lb/1000 lb	3.9 lb/1000 lb	4.0 lb/1000 lb	2.0 lb/1000 lb	7.8 lb/1000 lb	3.9 lb/1000 lb
TSS	11.0 lb/1000 lb	5.5 lb/1000 lb	2.0 lb/1000 lb	1.0 lb/1000 lb	7.8 lb/1000 lb	3.9 lb/1000 lb
COD	70.2 lb/1000 lb	35.1 lb/1000 lb	23.4 lb/1000 lb	11.7 lb/1000 lb	70.2 lb/1000 lb	35.1 lb/1000 lb
Total Chromium	0.04 lb/1000 lb	0.02 lb/1000 lb	0.04 lb/1000 lb	0.02 lb/1000 lb	0.04 lb/1000 lb	0.02 lb/1000 lb

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 410 - TEXTILE INDUSTRY (Continued)			FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74			
Subpart F - Carpet Mills Subcategory (Continued)						
(a) Manufacture of carpets through simple or complex manufacturing operations: (continued)						
Phenol	0.04 lb/1000 lb	0.02 lb/1000 lb	0.04 lb/1000 lb	0.02 lb/1000 lb	0.04 lb/1000 lb	0.02 lb/1000 lb
Sulfide	0.08 lb/1000 lb	0.04 lb/1000 lb	0.08 lb/1000 lb	0.04 lb/1000 lb	0.08 lb/1000 lb	0.04 lb/1000 lb
Color			Shall not exceed 225 APHA units.			
Fecal Coliform			MPN shall not exceed 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Manufacture of carpets through complex manufacturing operations, in addition to the discharge allowed by (a) of this section:						
COD	20 lb/1000 lb	10 lb/1000 lb	6.6 lb/1000 lb	3.3 lb/1000 lb	20 lb/1000 lb	10 lb/1000 lb
Subpart G - Stock and Yarn Dyeing and Finishing Subcategory						
(a)						
BOD5	6.8 lb/1000 lb	3.4 lb/1000 lb	4.6 lb/1000 lb	2.3 lb/1000 lb	6.8 lb/1000 lb	3.4 lb/1000 lb
TSS	17.4 lb/1000 lb	8.7 lb/1000 lb	3.8 lb/1000 lb	1.9 lb/1000 lb	6.8 lb/1000 lb	3.4 lb/1000 lb
COD	84.6 lb/1000 lb	42.3 lb/1000 lb	28.1 lb/1000 lb	14.1 lb/1000 lb	84.6 lb/1000 lb	42.3 lb/1000 lb
Total Chromium	0.12 lb/1000 lb	0.06 lb/1000 lb	0.12 lb/1000 lb	0.06 lb/1000 lb	0.12 lb/1000 lb	0.06 lb/1000 lb
Phenol	0.12 lb/1000 lb	0.06 lb/1000 lb	0.12 lb/1000 lb	0.06 lb/1000 lb	0.12 lb/1000 lb	0.06 lb/1000 lb
Sulfide	0.24 lb/1000 lb	0.12 lb/1000 lb	0.24 lb/1000 lb	0.12 lb/1000 lb	0.24 lb/1000 lb	0.12 lb/1000 lb
Color			Shall not exceed 300 APHA units.			

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 410 - TEXTILE INDUSTRY (Continued)	FINAL REGULATIONS, PUBLISHED 7/5/74, EFFECTIVE 7/5/74					
Subpart G - Stock and Yarn Dyeing and Finishing Subcategory (Continued)						
Fecal Coliform			MPN shall not exceed 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

(b) Additional allocations equal to the effluent limitations (except pH) established in (a) of this section are allowed any point source subject to such effluent limitations that dyes or finishes stock and yarn through "commission finishing" as defined.

Parameter	*BPT (Maximum for any 1 Day)	BAT (Maximum for any 1 Day)	New Sources (Maximum for any 1 Day)
PART 411 - CEMENT MANUFACTURING	FINAL REGULATIONS, PUBLISHED 2/20/74, EFFECTIVE 4/22/74		
Subpart A - Nonleaching Subcategory			
TSS	0.005 lb/1000 lb of product	0.005 lb/1000 lb of product	0.005 lb/1000 lb of product
Temperature	NTE 3°C rise above inlet temperature	NTE 3°C rise above inlet temperature	NTE 3°C rise above inlet temperature
pH	6.0 - 9.0	6.0 - 9.0	6.0 - 9.0
Subpart B - Leaching Subcategory			
TSS	0.4 lb/1000 lb of dust leached	0.005 lb/1000 lb of dust leached	0.4 lb/1000 lb of dust leached
Temperature	NTE 3°C rise above inlet temperature	NTE 3°C rise above inlet temperature	NTE 3°C rise above inlet temperature
pH	6.0 - 9.0	6.0 - 9.0	6.0 - 9.0
Subpart C - Materials Storage Piles Runoff Subcategory			
	(a) Subject to the provisions of sub-paragraph (b) of this section, the following limitations apply:	(a) Subject to the provisions of sub-paragraph (b) of this section, the following limitations apply:	No discharge of process waste water pollutants to navigable waters.
TSS	Not to exceed 50 mg/l	Not to exceed 50 mg/l	
pH	6.0 - 9.0	6.0 - 9.0	
	(b) Any untreated overflow from facilities designed constructed and operated to treat the volume of runoff from materials storage piles which is associated with a 10 year, 24 hour rainfall event shall not be subject to the pH and TSS limitations stipulated in subparagraph (a) above.	(b) Any untreated overflow from facilities designed constructed and operated to treat the volume of runoff from materials storage piles which results from a 10 year, 24 hour rainfall event shall not be subject to the pH and TSS limitations stipulated in subparagraph (a) above.	

Parameter	*BPT Daily	30 Day	Daily	BAT 30 Day	Daily	New Sources 30 Day

PART 412 - FEEDLOTS FINAL REGULATIONS, PUBLISHED 2/14/74, EFFECTIVE 4/15/74

Subpart A - All Subcategories Except Ducks

The provisions of this subpart are applicable to discharges of pollutants resulting from feedlots in the following subcategories: Beef cattle--open lots; beef cattle--housed lots; dairy cattle--stall barn (with milk room); dairy--free stall barn (with milking center); dairy--cowyards (with milking center); swine--open dirt or pasture lots; swine--housed, slotted floor; swine--solid concrete floor, open or housed lot; sheep--open lots; sheep--housed lots; horses--stables (race tracks); chickens--broilers, housed; chickens--layers (egg production), housed; chickens--layer breeding or replacement stock, housed; turkeys--open lots; turkeys--housed; and for those feedlot operations within these subcategories as large or larger than the capacities given below:

1,000 slaughter steers and heifers; 700 mature dairy cattle (whether milkers or dry cows); 2,500 swine weighing over 55 pounds; 10,000 sheep; 55,000 turkeys; 100,000 laying hens or broilers when facility has unlimited continuous flow watering systems; 30,000 laying hens or broilers when facility has liquid manure handling system; 500 horses; and 1,000 animal units from a combination of slaughter steers and heifers, mature dairy cattle, swine over 55 pounds and sheep.

(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants to navigable waters.	(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants to navigable waters.	(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants to navigable waters.
(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste waters plus the runoff from a 10 year, 24 hour rainfall event for the location of the point source.	(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste waters, plus the runoff from a 25 year, 24 hour rainfall event for the location of the point source.	(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic, or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste waters, plus the runoff from a 25 year, 24 hour rainfall event for the location of the point source.

Subpart B - Ducks Subcategory

The provisions of this subpart are applicable to discharges of pollutants resulting from feedlots for the following subcategories: ducks--dry lot; ducks--wet lot; and for those feedlot operations within these subcategories as large or larger than the capacities given below:

5000 ducks

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 412 - FEEDLOTS (Continued)	FINAL REGULATIONS, PUBLISHED 2/14/74, EFFECTIVE 4/15/74					
Subpart B - Oucks Subcategory (Continued)						
BOD5	3.66 lb/1000 ducks	2.00 lb/1000 ducks	(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants to navigable waters.		(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants to navigable waters.	
Fecal Coliform	NTE mpn of 400/100 ml at any time		(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste waters plus the runoff from a 25 year, 24 hour rainfall event for the location of the point source.		(b) Process waste pollutants in the overflow may be discharged to navigable waters whenever rainfall events, either chronic or catastrophic, cause an overflow of process waste water from a facility designed, constructed and operated to contain all process generated waste waters plus the runoff from a 25 year, 24 hour rainfall event for the location of the point source.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 413 - ELECTROPLATING	**FINAL REGULATIONS, PUBLISHED 3/28/74, EFFECTIVE 5/28/74**					
Subpart A - Electroplating of Copper, Nickel, Chromium, and Zinc on Ferrous and Nonferrous Materials Subcategory						
Cu	(a) 32.7 lb/million sq ft/ operation	16.4 lb/million sq ft/ operation	(a) There shall be no discharge of process waste water pollutants to navigable waters.		(a) 16.4 lb/million sq ft/operation	8.2 lb/million sq ft/operation
Ni	32.7 lb/million sq ft/ operation	16.4 lb/million sq ft/ operation			16.4 lb/million sq ft/operation	8.2 lb/million sq ft/operation
CrVI	3.3 lb/million sq ft/ operation	1.6 lb/million sq ft/ operation			1.6 lb/million sq ft/operation	.8 lb/million sq ft/operation
Cr, Total	32.7 lb/million sq ft/ operation	16.4 lb/million sq ft/ operation			16.4 lb/million sq ft/operation	**6.2 lb/million sq ft/operation
Zn	32.7 lb/million sq ft/ operation	16.4 lb/million sq ft/ operation			16.4 lb/million sq ft/operation	**8.2 lb/million sq ft/operation
CN,A	3.3 lb/million sq ft/ operation	1.6 lb/million sq ft/ operation			1.6 lb/million sq ft/operation	.8 lb/million sq ft/operation
CN, Total	32.7 lb/million sq ft/ operation	16.4 lb/million sq ft/ operation			**16.4 lb/million sq ft/operation	4.7 lb/million sq ft/operation
TSS	982.0 lb/million sq ft/ operation	654.0 lb/million sq ft/ operation			491.0 lb/million sq ft/operation	327.0 lb/million sq ft/operation
pH	6.0 - 9.5				6.0 - 9.5	

(b) Pursuant to section 308 of the Act, point sources subject to the provisions of this subpart shall maintain records of production expressed in sq m or sq ft for the purpose of determining compliance with the above limitations. For the purpose of complying with the requirements of this paragraph, a discharger may establish a correlation between area plated and another parameter, such as ampere-hours used in plating.

(b) Application of the factors listed in section 304(b) of the Act may require variation from the effluent limitation set forth in this section for any point source subject to such effluent limitation with a production less than 120 sq m per hour. If variation is determined to be necessary for any such source, such source shall be subject to effluent limitations no less stringent than those required by the standards of performance for new sources

**Corrected per 39 FR 26642, July 22, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 413 - ELECTROPLATING (Continued)	FINAL REGULATIONS, PUBLISHED 3/28/74, EFFECTIVE 5/28/74					
Subpart A - Electroplating of Copper, Nickel, Chromium, and Zinc on Ferrous and Nonferrous Materials Subcategory						
(c) Application of the factors listed in section 304(b) requires variation from the effluent limitations set forth above for any point source subject to such effluent limitations with a production less than 33 square meters per hour or an installed direct current capacity less than 2000 amperes. For such sources, the best practicable control technology currently available consists of cyanide destruction, if any, equalization and pH adjustment to a range of 6.0 to 9.5** prior to discharge.						

**Corrected per 39 FR 26642, July 22, 1974

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 414 - ORGANIC CHEMICALS	FINAL REGULATIONS, PUBLISHED 4/25/74, EFFECTIVE 5/13/74 (All references to lb/1000 lb are to 1000 lb of product)					
Subpart A - Nonaqueous Processes Subcategory						
BOD5	0.045 lb/1000 lb	0.02 lb/1000 lb	.015 lb/1000 lb	.0085 lb/1000 lb	0.037 lb/1000 lb	0.017 lb/1000 lb
TSS	.067 lb/1000 lb	.03 lb/1000 lb	.022 lb/1000 lb	.013 lb/1000 lb	.034 lb/1000 lb	.015 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
COD			0.062 lb/1000 lb	0.045 lb/1000 lb		
Subpart B - Processes with Process Water Contact as Steam Diluent or Absorbent Subcategory						
(a) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged from the manufacture of acetone, butadiene (co-product of ethylene), ethyl benezene, ethylene and propylene, ethylene dichloride, ethylene oxide, formaldehyde, methanol, methyl amines, vinyl acetate, or vinyl chloride (cracking of ethylene dichloride) by a point source subject to the provisions of this subpart.						
COD			0.80 lb/1000 lb	0.58 lb/1000 lb		
BOD5	0.13 lb/1000 lb	0.058 lb/1000 lb	.044 lb/1000 lb	.025 lb/1000 lb	0.11 lb/1000 lb	0.048 lb/1000 lb
TSS	.20 lb/1000 lb	.088 lb/1000 lb	.066 lb/1000 lb	.040 lb/1000 lb	.10 lb/1000 lb	.044 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged from the manufacture of acetaldehyde (dehydrogenation of ethano)), acetylene (partial oxidation of methane), butadiene (dehydrogenation of n-butane), butadiene (oxidative-dehydrogenation of butylene**)or styrene by a point source subject to the provisions of this subpart.						
COD			1.32 lb/1000 lb	0.95 lb/1000 lb		
BOD5	0.95 lb/1000 lb	0.42 lb/1000 lb	.32 lb/1000 lb	.18 lb/1000 lb	0.76 lb/1000 lb	0.34 lb/1000 lb
TSS	1.42 lb/1000 lb	.64 lb/1000 lb	.48 lb/1000 lb	.29 lb/1000 lb	.72 lb/1000 lb	**.32 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 20597, June 12, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 414 - ORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 4/25/74, EFFECTIVE 5/13/74			
Subpart C - Aqueous Liquid Phase Reaction Systems Subcategory						
(a) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged from the manufacture of acetic acid, acrylic acid, coal tar (distillation), ethylene glycol, terephthalic acid (oxidation of p-xylene), or polymer grade terephthalic acid (purification of terephthalic acid) by a point source subject to the provisions of this subpart.						
COD			0.52 lb/1000 lb	0.37 lb/1000 lb		
BOD5	0.28 lb/1000 lb	0.12 lb/1000 lb	.093 lb/1000 lb	.053 lb/1000 lb	0.23 lb/1000 lb	0.10 lb/1000 lb
TSS	.42 lb/1000 lb	.19 lb/1000 lb	.14 lb/1000 lb	.085 lb/1000 lb	.21 lb/1000 lb	**.094 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged from the manufacture of acetaldehyde (oxidation of ethylene with oxygen), caprolactam, coal tar (pitch forming), oxo chemicals, or phenol and acetone (cumene process) by a point source subject to the provisions of this subpart.						
COD			1.75 lb/1000 lb	0.98 lb/1000 lb		
BOD5	0.55 lb/1000 lb	0.25 lb/1000 lb	.12 lb/1000 lb	.068 lb/1000 lb	0.45 lb/1000 lb	0.20 lb/1000 lb
TSS	.56 lb/1000 lb	.25 lb/1000 lb	.19 lb/1000 lb	.11 lb/1000 lb	.28 lb/1000 lb	.12 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph which may be discharged from the manufacture of acetaldehyde (oxidation of ethylene with air), aniline, bisphenol A, or dimethyl terephthalate by a point source subject to the provisions of this subpart.						
COD			6.07 lb/1000 lb	4.37 lb/1000 lb		
BOD5	1.15 lb/1000 lb	0.51 lb/1000 lb	.067 lb/1000 lb	.043 lb/1000 lb	0.94 lb/1000 lb	0.42 lb/1000 lb
TSS	.15 lb/1000 lb	.068 lb/1000 lb	.05 lb/1000 lb	.03 lb/1000 lb	.076 lb/1000 lb	.034 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 20597, June 12, 1974

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 414 - ORGANIC CHEMICALS (Continued)	FINAL REGULATIONS, PUBLISHED 4/25/74, EFFECTIVE 5/13/74					
Subpart C - Aqueous Liquid Phase Reaction Systems Subcategory (Continued)						
(d) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph which may be discharged from the manufacture of acrylates, p-cresol, methyl methacrylate, terephthalic acid (nitric acid process) or tetraethyl lead by a point source subject to the provisions of this subpart.						
COD			39.25 lb/1000 lb	28.26 lb/1000 lb		
BOD5	3.08 lb/1000 lb	1.37 lb/1000 lb	.62 lb/1000 lb	.35 lb/1000 lb	2.56 lb/1000 lb	1.14 lb/1000 lb
TSS	2.80 lb/1000 lb	1.25 lb/1000 lb	.94 lb/1000 lb	.57 lb/1000 lb	1.40 lb/1000 lb	.63 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(e) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged from the manufacture of phenol and acetone, bisphenol A, or p-cresol by a point source subject to the provision of this subpart.						
Phenols	0.045 lb/1000 lb	0.020 lb/1000 lb	0.003 lb/1000 lb	0.017 lb/1000 lb	0.045 lb/1000 lb	0.02 lb/1000 lb

**Corrected per 39 FR 20597, June 12, 1974

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS	FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74					
Subpart A - Aluminum Chloride Production Subcategory	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart B - Aluminum Sulfate Production Subcategory	(a) Subject to the provisions of paragraphs (b), (c), and (d) of this section, there shall be no discharge of process waste water pollutants to navigable waters. (b) A process waste water impoundment which is designed, constructed and operated so as to contain the precipitation from the 10 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 10 year, 24 hour rainfall event when such event occurs. (c) During any calendar month there may be discharged from a process waste water impoundment either a volume of process waste water equal to the difference between the precipitation for that month that falls within the impoundment and the evaporation for that month, or, if greater, a volume of process		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)		FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74				
	waste water equal to the difference between the mean precipitation for that month that falls within the impoundment and the mean evaporation for that month as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located (or as otherwise determined if no monthly data have been established by the National Climatic Center). (d) Any process waste water discharged pursuant to paragraph (c) of this section shall comply with each of the following requirements:					
TSS	50 ppm	25 ppm				
pH	6.0 - 9.0					
Subpart C - Calcium Carbide Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart D - Calcium Chloride Production Subcategory						
TSS	0.016 lb/1000 lb of prod.	0.0082 lb/1000 lb of prod.	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
pH	6.0 - 9.0					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)	FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74					
Subpart E - Calcium Oxide and Calcium Hydroxide Production Subcategory						
	(a) Subject to the provisions of paragraphs (b), (c), and (d) of this section, there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed and operated so as to contain the precipitation from the 10 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 10 year, 24 hour rainfall event, when such event occurs. (c) During any calendar month there may be discharged from a process waste water impoundment either a volume of process waste water equal to the difference between the precipitation for that month that falls within the impoundment and the evaporation for that month, or, if greater, a volume of process waste water equal to the difference between the mean precipitation for that month that falls within the impoundment and the mean evaporation for that month as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located (or as other-		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74			
	wise determined if no monthly data have been established by the National Climatic Center). (d) Any process waste water discharged pursuant to paragraph (c) of this section shall comply with each of the following requirements:					
TSS	50 ppm	25 ppm				
pH	6.0 - 9.0					
Subpart F - Chlorine and Sodium or Potassium Hydroxide Production Subcategory						
(a) Chlorine and Sodium or Potassium Hydroxide Manufacture by the Mercury Cell Process:						
TSS	0.64 lb/1000 lb of product	0.32 lb/1000 lb of product	(1) Subject to the provisions of paragraph (a)(2) of this section there shall be no discharge of process waste water pollutants into navigable waters. (2) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		0.64 lb/1000 lb of product	0.32 lb/1000 lb of product
Mercury	.00028 lb/1000 lb of product	.00014 lb/1000 lb of product			.00014 lb/1000 lb of product	.00007 lb/1000 lb of product
pH	6.0 - 9.0				6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74			
(b) Chlorine and Sodium or Potassium Hydroxide Manufacture by the Diaphragm Cell Process:						
TSS	0.64 lb/1000 lb of product	0.32 lb/1000 lb of product	There shall be no discharge of process waste water pollutants to navigable waters.		0.64 lb/1000 lb of product	0.32 lb/1000 lb of product
Lead	.005 lb/1000 lb of product	.0025 lb/1000 lb of product			.00008 lb/1000 lb of product	.00004 lb/1000 lb of product
pH	6.0 - 9.0				6.0 - 9.0	
Subpart G - Hydrochloric Acid Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart H - Hydrofluoric Acid Production Subcategory						
	(a) Subject to the provisions of paragraphs (b), (c), and (d) of this section, there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed and operated so as to contain the precipitation from the 10 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 10 year, 24 hour rainfall event, when such event occurs.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)	FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74					
	(c) During any calendar month there may be discharged from a process waste water impoundment either a volume of process waste water equal to the difference between the precipitation for that month that falls within the impoundment and the evaporation for that month, or, if greater, a volume of process waste water equal to the difference between the mean precipitation for that month that falls within the impoundment and the mean evaporation for that month as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located (or as otherwise determined if no monthly data have been established by the National Climatic Center). (d) Any process waste water discharged pursuant to paragraph (c) of this section shall comply with each of the following requirements:					
Fluoride	30 ppm	15 ppm				
TSS	50 ppm	25 ppm				
pH	6.0 - 9.0					
Subpart I - Hydrogen Peroxide Production Subcategory						
(a) Hydrogen Peroxide Manufacture by the Oxidation of Alkyl Hydroanthraquinones						
TSS	0.8 lb/1000 lb of product	0.4 lb/1000 lb of product	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
TOC	.44 lb/1000 lb of product	.22 lb/1000 lb of product				
pH	6.0 - 9.0					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74			
(b) Hydrogen Peroxide Manufacture by the Electrolytic Process						
TSS	0.005 lb/1000 lb of product	0.0025 lb/1000 lb of product	(1) Subject to the provisions of paragraph (b)(2) of this section there shall be no discharge of process waste water pollutants into navigable waters.		(1) Subject to the provisions of paragraph (b)(2) of this section there shall be no discharge of process waste water pollutants into navigable waters.	
Cyanide A	.0004 lb/1000 lb of product	.0002 lb/1000 lb of product				
pH	6.0 - 9.0					
			(2) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(2) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	
Subpart J - Nitric Acid Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart K - Potassium Metal Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart L - Potassium Dichromate Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)	FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74					
Subpart M - Potassium Sulfate Production Subcategory						
	(a) Subject to the provisions of paragraphs (b), (c), and (d) of this section, there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed and operated so as to contain the precipitation from the 10 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 10 year, 24 hour rainfall event, when such event occurs. (c) During any calendar month there may be discharged from a process waste water impoundment either a volume of process waste water equal to the difference between the precipitation for that month that falls within the impoundment and the evaporation for that month, or, if greater, a volume of process waste water equal to the difference between the mean precipitation for that month that falls within the impoundment and the mean evaporation for that month as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located (or as otherwise determined if no monthly data have been established by the National Climatic Center).		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters. (b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74			
	(d) Any process waste water discharged pursuant to paragraph (c) of this section shall comply with each of the following requirements:					
TSS	50 ppm	25 ppm				
pH	6.0 - 9.0					
Subpart N - Sodium Bicarbonate Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters	
Subpart O - Sodium Carbonate Production Subcategory						
TSS	**0.34 lb/1000 lb of product	**0.17 lb/1000 lb of product	**0.20 lb/1000 lb of product	**0.10 lb/1000 lb of product	There shall be no discharge of process waste water pollutants to navigable waters	
pH	6.0 - 9.0		6.0 - 9.0			
Subpart P - Sodium Chloride Production Subcategory						
	(a) Manufacture by solar evaporative process: there shall be no discharge of process waste water pollutants to navigable waters, except that unused bitterns may be returned to the body of water from which the process brine solution was originally withdrawn, provided no additional pollutants are added to the bitterns during the production of sodium chloride.		(a) Manufacture by solar evaporative process: there shall be no discharge of process waste water pollutants to navigable waters, except that unused bitterns may be returned to the body of water from which the process brine solution was originally withdrawn, provided no additional pollutants are added to the bitterns during the production of sodium chloride.		(a) Manufacture by solar evaporative process: there shall be no discharge of process waste water pollutants to navigable waters, except that unused bitterns may be returned to the body of water from which the process brine solution was originally withdrawn, provided no additional pollutants are added to the bitterns during the production of sodium chloride.	
	(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged in process waste water from sodium chloride manufacture by the solution brinemining process:		(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged in process waste water from sodium chloride manufacture by the solution brinemining process: there shall be no discharge of process waste water pollutants to navigable waters.		(b) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged in process waste water from sodium chloride manufacture by the solution brine-mining process: there shall be no discharge of process waste water pollutants to navigable waters.	
TSS	0.34 lb/1000 lb of product	0.17 lb/1000 lb of product				
pH	6.0 - 9.0					

**Corrected per 39 FR 20376, June 10, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74			
Subpart Q - Sodium Dichromate and Sodium Sulfate Production Subcategory						
TSS	0.44 lb/1000 lb of product	0.22 lb/1000 lb of product			0.30 lb/1000 lb of product	0.15 lb/1000 lb of product
Cr(+6)	.009 lb/1000 lb of product	.0005 lb/1000 lb of product			0.009 lb/1000 lb of product	0.0005 lb/1000 lb of product
Cr(T)	.0088 lb/1000 lb of product	.0044 lb/1000 lb of product			0.0088 lb/1000 lb of product	0.0044 lb/1000 lb of product
pH	6.0 - 9.0				6.0 - 9.0	
Subpart R - Sodium Metal Production Subcategory						
TSS	0.46 lb/1000 lb of product	0.23 lb/1000 lb of product				
pH	6.0 - 9.0					

(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.

(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.

(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.

(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the

(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.

(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)			FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74			
			impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	
Subpart S - Sodium Silicate Production Subcategory						
TSS	0.01 lb/1000 lb of product	0.005 lb/1000 lb of product	(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.	
pH	6.0 - 9.0		(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	
Subpart T - Sodium Sulfite Production Subcategory						
TSS	0.032 lb/1000 lb of product	0.016 lb/1000 lb of product	(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters	
COD	3.4 lb/1000 lb of product	1.7 lb/1000 lb of product				
pH	6.0 - 9.0		(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National			

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 415 - INORGANIC CHEMICALS (Continued)	FINAL REGULATIONS, PUBLISHED 3/12/74, EFFECTIVE 5/13/74					
			Oceanic and Atmospheric Administration for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.			
Subpart U - Sulfuric Acid Production Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart V - Titanium Dioxide Production Subcategory						
(a) Titanium Dioxide Manufacture by the Chloride Process:						
TSS	4.6 lb/1000 lb of product	2.3 lb/1000 lb of product	2.6 lb/1000 lb of product	1.3 lb/1000 lb of product	2.6 lb/1000 lb of product	1.3 lb/1000 lb of product
Iron	.72 lb/1000 lb of product	.36 lb/1000 lb of product	.36 lb/1000 lb of product	.18 lb/1000 lb of product	.36 lb/1000 lb of product	.18 lb/1000 lb of product
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Titanium Dioxide Manufactured by the Sulfate Process:						
TSS	21.0 lb/1000 lb of product	10.5 lb/1000 lb of product	10.6 lb/1000 lb of product	5.3 lb/1000 lb of product	10.6 lb/1000 lb of product	5.3 lb/1000 lb of product
Iron	1.7 lb/1000 lb of product	.84 lb/1000 lb of product	.84 lb/1000 lb of product	.42 lb/1000 lb of product	.84 lb/1000 lb of product	.42 lb/1000 lb of product
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS	FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74 (All references to lb/1000 lb are to 1000 lb of product)					
Subpart A - Polyvinyl Chloride Subcategory						
(a) Limitations for discharge from the manufacture of polyvinyl chloride by the suspension polymerization process:						
BOD5	0.70 lb/1000 lb	0.36 lb/1000 lb	0.41 lb/1000 lb	0.28 lb/1000 lb	0.37 lb/1000 lb	0.19 lb/1000 lb
COD	7.0 lb/1000 lb	3.6 lb/1000 lb	1.92 lb/1000 lb	1.28 lb/1000 lb	1.70 lb/1000 lb	.89 lb/1000 lb
TSS	1.8 lb/1000 lb	.99 lb/1000 lb	.23 lb/1000 lb	.19 lb/1000 lb	.19 lb/1000 lb	.13 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Limitations for discharge from the manufacture of polyvinyl chloride by the emulsion polymerization process:						
BOD5	0.26 lb/1000 lb	0.13 lb/1000 lb	0.20 lb/1000 lb	0.13 lb/1000 lb	0.26 lb/1000 lb	0.13 lb/1000 lb
COD	2.6 lb/1000 lb	1.3 lb/1000 lb	.92 lb/1000 lb	.61 lb/1000 lb	1.20 lb/1000 lb	.61 lb/1000 lb
TSS	.65 lb/1000 lb	.36 lb/1000 lb	.11 lb/1000 lb	.092 lb/1000 lb	.14 lb/1000 lb	.092 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c) Limitations for discharge from the manufacture of polyvinyl chloride by the bulk polymerization process:						
BOD5	0.12 lb/1000 lb	0.06 lb/1000 lb	0.09 lb/1000 lb	0.06 lb/1000 lb	0.12 lb/1000 lb	0.06 lb/1000 lb
COD	1.2 lb/1000 lb	.60 lb/1000 lb	.42 lb/1000 lb	.28 lb/1000 lb	.54 lb/1000 lb	.28 lb/1000 lb
TSS	.29 lb/1000 lb	.16 lb/1000 lb	.05 lb/1000 lb	.042 lb/1000 lb	.06 lb/1000 lb	.042 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/6/74			
Subpart B - Polyvinyl Acetate Subcategory						
BOD5	0.39 lb/1000 lb	0.20 lb/1000 lb	0.29 lb/1000 lb	0.19 lb/1000 lb	0.35 lb/1000 lb	0.18 lb/1000 lb
COD	3.9 lb/1000 lb	2.0 lb/1000 lb	1.33 lb/1000 lb	.89 lb/1000 lb	1.6 lb/1000 lb	.84 lb/1000 lb
TSS	1.0 lb/1000 lb	.55 lb/1000 lb	.16 lb/1000 lb	.14 lb/1000 lb	.19 lb/1000 lb	.13 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart C - Polystyrene Subcategory						
(a) Limitations for discharge from the manufacture of polystyrene by the suspension polymerization process:						
BOD5	0.43 lb/1000 lb	0.22 lb/1000 lb	0.33 lb/1000 lb	0.22 lb/1000 lb	0.43 lb/1000 lb	0.22 lb/1000 lb
COD	4.3 lb/1000 lb	2.20 lb/1000 lb	1.55 lb/1000 lb	1.03 lb/1000 lb	2.0 lb/1000 lb	1.03 lb/1000 lb
Total Chromium	.0046 lb/1000 lb	.0023 lb/1000 lb	.0046 lb/1000 lb	.0023 lb/1000 lb	.0046 lb/1000 lb	.0023 lb/1000 lb
TSS	1.1 lb/1000 lb	.61 lb/1000 lb	.18 lb/1000 lb	.16 lb/1000 lb	.24 lb/1000 lb	.16 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Limitations for discharge from the manufacture of polystyrene by bulk polymerization process:						
BOD5	0.08 lb/1000 lb	0.04 lb/1000 lb	0.06 lb/1000 lb	0.04 lb/1000 lb	0.08 lb/1000 lb	0.04 lb/1000 lb
COD	.80 lb/1000 lb	.40 lb/1000 lb	.29 lb/1000 lb	.19 lb/1000 lb	.37 lb/1000 lb	.19 lb/1000 lb
TSS	.20 lb/1000 lb	.11 lb/1000 lb	.033 lb/1000 lb	.028 lb/1000 lb	.04 lb/1000 lb	.028 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart D - Polypropylene Subcategory						
BOD5	0.81 lb/1000 lb	0.42 lb/1000 lb	0.48 lb/1000 lb	0.32 lb/1000 lb	0.43 lb/1000 lb	0.22 lb/1000 lb
COD	4.1 lb/1000 lb	2.1 lb/1000 lb	3.21 lb/1000 lb	2.14 lb/1000 lb	2.9 lb/1000 lb	1.47 lb/1000 lb
TSS	2.3 lb/1000 lb	1.16 lb/1000 lb	.27 lb/1000 lb	.23 lb/1000 lb	.24 lb/1000 lb	.16 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Polyethylene Subcategory						
(a) Limitations for discharge from the manufacture of low density polyethylene:						
BOD5	0.39 lb/1000 lb	0.20 lb/1000 lb	0.29 lb/1000 lb	0.19 lb/1000 lb	0.35 lb/1000 lb	0.18 lb/1000 lb
COD	3.9 lb/1000 lb	2.0 lb/1000 lb	2.48 lb/1000 lb	1.65 lb/1000 lb	3.5 lb/1000 lb	1.80 lb/1000 lb
TSS	1.0 lb/1000 lb	.55 lb/1000 lb	.16 lb/1000 lb	.14 lb/1000 lb	.19 lb/1000 lb	.13 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Limitations for discharge from the manufacture of high density polyethylene by the solvent process:						
BOD5	0.58 lb/1000 lb	0.30 lb/1000 lb	0.45 lb/1000 lb	0.30 lb/1000 lb	0.58 lb/1000 lb	0.3 lb/1000 lb
COD	5.8 lb/1000 lb	3.0 lb/1000 lb	2.40 lb/1000 lb	1.60 lb/1000 lb	3.1 lb/1000 lb	1.6 lb/1000 lb
Total Chromium	.0062 lb/1000 lb	.0031 lb/1000 lb	.0062 lb/1000 lb	.0031 lb/1000 lb	.0062 lb/1000 lb	.0031 lb/1000 lb
TSS	1.5 lb/1000 lb	.83 lb/1000 lb	.25 lb/1000 lb	.21 lb/1000 lb	.31 lb/1000 lb	.21 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT		BAT		New Sources	
	Daily	30 Day	Daily	30 Day	Daily	30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart E - Polyethylene Subcategory (Continued)						
(c) Limitations for discharge from the manufacture of high density polyethylene by the polyform process:						
BOD5	0.10 lb/1000 lb	0.052 lb/1000 lb	0.078 lb/1000 lb	0.052 lb/1000 lb	0.10 lb/1000 lb	0.054 lb/1000 lb
COD	1.0 lb/1000 lb	.52 lb/1000 lb	.42 lb/1000 lb	.28 lb/1000 lb	.56 lb/1000 lb	.28 lb/1000 lb
TSS	.25 lb/1000 lb	.14 lb/1000 lb	**.043 lb/1000 lb	**.037 lb/1000 lb	.05 lb/1000 lb	.036 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart F - Cellophane Subcategory						
BOD5	17.8 lb/1000 lb	8.7 lb/1000 lb	**7.9 lb/1000 lb	**5.1 lb/1000 lb	**7.41 lb/1000 lb	**3.6 lb/1000 lb
COD	178.0 lb/1000 lb	87.0 lb/1000 lb	**68.3 lb/1000 lb	**43.9 lb/1000 lb	**98 lb/1000 lb	**48 lb/1000 lb
TSS	29.1 lb/1000 lb	16.0 lb/1000 lb	3.75 lb/1000 lb	3.19 lb/1000 lb	3.3 lb/1000 lb	2.27 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart G - Rayon Subcategory						
BOD5	10.0 lb/1000 lb	4.8 lb/1000 lb	**4.4 lb/1000 lb	**2.8 lb/1000 lb	**4.171b/1000 lb	**2.0 lb/1000 lb
COD	150.0 lb/1000 lb	72.0 lb/1000 lb	**37.9 lb/1000 lb	**24.4 lb/1000 lb	**97 lb/1000 lb	**47.0 lb/1000 lb
Zinc	.91 lb/1000 lb	.534 lb/1000 lb	0.210 lb/1000 lb	0.105 lb/1000 lb	0.15 lb/1000 lb	0.075 lb/1000 lb
TSS	16.0 lb/1000 lb	8.8 lb/1000 lb	2.08 lb/1000 lb	1.77 lb/1000 lb	1.9 lb/1000 lb	1.28 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24593, July 8, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart H - Acrylonitrile-Butadiene-Styrene (ABS) and Styrene-Acrylonitrile (SAN) Resin Copolymers						
BOD5	1.3 lb/1000 lb	0.63 lb/1000 lb	**.70 lb/1000 lb	**.45 lb/1000 lb	**.88 lb/1000 lb	**.43 lb/1000 lb
COD	13.0 lb/1000 lb	6.3 lb/1000 lb	**5.1 lb/1000 lb	**3.3 lb/1000 lb	**6.5 lb/1000 lb	**3.1 lb/1000 lb
TSS	2.1 lb/1000 lb	1.16 lb/1000 lb	0.33 lb/1000 lb	0.28 lb/1000 lb	0.40 lb/1000 lb	0.27 lb/1000 lb
Total Chromium	.0088 lb/1000 lb	.0044 lb/1000 lb	0.0084 lb/1000 lb	0.0042 lb/1000 lb	0.0080 lb/1000 lb	0.0040 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart I - Polyester Subcategory						
(a) Limitations for discharge from the manufacture of polyester resin by batch processing:						
BOD5	1.4 lb/1000 lb	0.78 lb/1000 lb	**.59 lb/1000 lb	**.44 lb/1000 lb	**.79 lb/1000 lb	**.44 lb/1000 lb
COD	21.5 lb/1000 lb	11.7 lb/1000 lb	**3.1 lb/1000 lb	**2.3 lb/1000 lb	**7.3 lb/1000 lb	**4.0 lb/1000 lb
TSS	.95 lb/1000 lb	.52 lb/1000 lb	0.16 lb/1000 lb	0.13 lb/1000 lb	0.19 lb/1000 lb	0.13 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Limitations for discharge from the manufacture of polyester fiber by batch processing:						
BOD5	1.4 lb/1000 lb	0.78 lb/1000 lb	**.59 lb/1000 lb	**.44 lb/1000 lb	**.79 lb/1000 lb	**.44 lb/1000 lb
COD	21.5 lb/1000 lb	11.7 lb/1000 lb	**3.1 lb/1000 lb	**2.3 lb/1000 lb	**7.3 lb/1000 lb	**4.0 lb/1000 lb
TSS	.95 lb/1000 lb	.52 lb/1000 lb	0.16 lb/1000 lb	0.13 lb/1000 lb	0.19 lb/1000 lb	0.13 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24893, July 8, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart I - Polyester Subcategory (Continued)						
(c) Limitations for discharge from the manufacture of polyester resin and fiber by continuous processing:						
BOD5	1.4 lb/1000 lb	0.78 lb/1000 lb	**.47 lb/1000 lb	**.34 lb/1000 lb	**.46 lb/1000 lb	**.25 lb/1000 lb
COD	21.5 lb/1000 lb	11.7 lb/1000 lb	**2.4 lb/1000 lb	**1.8 lb/1000 lb	**4.2 lb/1000 lb	**2.32 lb/1000 lb
TSS	.95 lb/1000 lb	.52 lb/1000 lb	**0.13 lb/1000 lb	**0.11 lb/1000 lb	0.12 lb/1000 lb	0.078 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(d) Limitations for discharge from the manufacture of polyester resin and fiber by batch processing:						
BOD5	2.8 lb/1000 lb	1.56 lb/1000 lb	**1.2 lb/1000 lb	**.87 lb/1000 lb	**1.58 lb/1000 lb	**.87 lb/1000 lb
COD	43.0 lb/1000 lb	23.4 lb/1000 lb	**6.2 lb/1000 lb	**4.5 lb/1000 lb	**14.6 lb/1000 lb	**8.0 lb/1000 lb
TSS	1.9 lb/1000 lb	1.04 lb/1000 lb	**0.32 lb/1000 lb	**0.27 lb/1000 lb	**0.4 lb/1000 lb	**0.27 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart J - Nylon 66 Subcategory						
(a) Limitations for discharge from the manufacture of nylon 66 resin:						
BOD5	1.2 lb/1000 lb	0.66 lb/1000 lb	**.5 lb/1000 lb	**.37 lb/1000 lb	**.67 lb/1000 lb	**.37 lb/1000 lb
COD	6.0 lb/1000 lb	3.3 lb/1000 lb	**2.6 lb/1000 lb	**1.9 lb/1000 lb	**4.8 lb/1000 lb	**2.6 lb/1000 lb
TSS	.80 lb/1000 lb	.44 lb/1000 lb	**0.13 lb/1000 lb	**0.11 lb/1000 lb	**0.16 lb/1000 lb	**0.11 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24893, July 8, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart J - Nylon 66 Subcategory (Continued)						
(b) Limitations for discharge from the manufacture of nylon 66 fiber:						
BOD5	1.1 lb/1000 lb	0.58 lb/1000 lb	**.44 lb/1000 lb	**.32 lb/1000 lb	**.58 lb/1000 lb	**.32 lb/1000 lb
COD	5.3 lb/1000 lb	3.0 lb/1000 lb	**2.3 lb/1000 lb	**1.7 lb/1000 lb	**4.2 lb/1000 lb	**2.3 lb/1000 lb
TSS	.70 lb/1000 lb	.39 lb/1000 lb	**0.12 lb/1000 lb	**0.10 lb/1000 lb	**0.15 lb/1000 lb	**0.10 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c) Limitations for discharge from the manufacture of nylon 66 resin and fiber:						
BOD5	2.3 lb/1000 lb	1.24 lb/1000 lb	**.94 lb/1000 lb	**.69 lb/1000 lb	**1.25 lb/1000 lb	**.69 lb/1000 lb
COD	11.3 lb/1000 lb	6.2 lb/1000 lb	**4.9 lb/1000 lb	**3.6 lb/1000 lb	**9.0 lb/1000 lb	**4.95 lb/1000 lb
TSS	1.5 lb/1000 lb	.83 lb/1000 lb	**0.25 lb/1000 lb	**0.21 lb/1000 lb	**0.31 lb/1000 lb	**0.21 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart K - Nylon 6 Subcategory						
(a) Limitations for discharge from the manufacture of nylon 6 resin:						
BOD5	6.8 lb/1000 lb	3.71 lb/1000 lb	**2.45 lb/1000 lb	**1.8 lb/1000 lb	**2.75lb/1000 lb	**1.51 lb/1000 lb
COD	68.0 lb/1000 lb	37.1 lb/1000 lb	**12.7 lb/1000 lb	**9.3 lb/1000 lb	**28.6 lb/1000 lb	**15.7 lb/1000 lb
TSS	4.5 lb/1000 lb	2.48 lb/1000 lb	**0.65 lb/1000 lb	**0.55 lb/1000 lb	**0.69 lb/1000 lb	**0.47 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24893, July 8, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart K - Nylon 6 Subcategory (Continued)						
(b) Limitations for discharge from the manufacture of nylon 6 fiber:						
BOD5	3.5 lb/1000 lb	1.90 lb/1000 lb	1.00 lb/1000 lb	0.67 lb/1000 lb	**1.42 lb/1000 lb	**.78 lb/1000 lb
COD	35.0 lb/1000 lb	19.0 lb/1000 lb	5.21 lb/1000 lb	3.44 lb/1000 lb	**14.7 lb/1000 lb	**8.1 lb/1000 lb
TSS	2.3 lb/1000 lb	1.27 lb/1000 lb	.33 lb/1000 lb	.28 lb/1000 lb	**0.35 lb/1000 lb	**0.24 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c) Limitations for discharge from the manufacture of nylon 6 resin and fiber:						
BOD5	10.3 lb/1000 lb	5.61 lb/1000 lb	2.95 lb/1000 lb	1.97 lb/1000 lb	**4.17 lb/1000 lb	**2.29 lb/1000 lb
COD	103.0 lb/1000 lb	56.1 lb/1000 lb	15.3 lb/1000 lb	10.2 lb/1000 lb	**43.4 lb/1000 lb	**23.9 lb/1000 lb
TSS	6.8 lb/1000 lb	3.75 lb/1000 lb	.98 lb/1000 lb	.84 lb/1000 lb	1.1 lb/1000 lb	**0.71 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart L - Cellulose Acetate Subcategory						
(a) Limitations for discharge from the manufacture of cellulose acetate resin:						
BOD5	7.5 lb/1000 lb	4.13 lb/1000 lb	1.88 lb/1000 lb	1.25 lb/1000 lb	**2.08 lb/1000 lb	**1.15 lb/1000 lb
COD	75.0 lb/1000 lb	41.3 lb/1000 lb	9.75 lb/1000 lb	6.5 lb/1000 lb	**20 lb/1000 lb	**11 lb/1000 lb
TSS	5.0 lb/1000 lb	2.75 lb/1000 lb	.63 lb/1000 lb	.53 lb/1000 lb	**0.51 lb/1000 lb	0.35 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24893, July 8, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 416 - PLASTICS AND SYNTHETICS (Continued)			FINAL REGULATIONS, PUBLISHED 4/5/74, EFFECTIVE 6/4/74			
Subpart L - Cellulose Acetate Subcategory (Continued)						
(b) Limitations for discharge from the manufacture of cellulose acetate fiber:						
BOD5	7.5 lb/1000 lb	4.13 lb/1000 lb	1.88 lb/1000 lb	1.25 lb/1000 lb	**2.08 lb/1000 lb	**1.15 lb/1000 lb
COD	75.0 lb/1000 lb	41.3 lb/1000 lb	9.75 lb/1000 lb	6.5 lb/1000 lb	**20 lb/1000 lb	**11 lb/1000 lb
TSS	5.0 lb/1000 lb	2.75 lb/1000 lb	.63 lb/1000 lb	.53 lb /1000 lb	0.51 lb/1000 lb	0.35 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c) Limitations for discharge from the manufacture of cellulose acetate resin and fiber:						
BOD5	15.0 lb/1000 lb	8.26 lb/1000 lb	3.75 lb/1000 lb	2.50 lb/1000 lb	**4.17 lb/1000 lb	**2.29 lb/1000 lb
COD	150.0 lb/1000 lb	82.6 lb/1000 lb	19.5 lb/1000 lb	13.0 lb/1000 lb	**40 lb/1000 lb	**22 lb/1000 lb
TSS	10.0 lb/1000 lb	5.50 lb/1000 lb	1.26 lb/1000 lb	1.06 lb/1000 lb	1.1 lb/1000 lb	0.71 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart M - Acrylics Subcategory						
BOD5	5.0 lb/1000 lb	2.75 lb/1000 lb	0.98 lb/1000 lb	0.65 lb/1000 lb	**1.58 lb/1000 lb	**.87 lb/1000 lb
COD	25.0 lb/1000 lb	13.8 lb/1000 lb	5.07 lb/1000 lb	3.38 lb/1000 lb	**30.4 lb/1000 lb	**16.7 lb/1000 lb
TSS	2.0 lb/1000 lb	1.1 lb/1000 lb	.33 lb/1000 lb	.27 lb/1000 lb	**0.4 lb/1000 lb	**0.27 lb/1000 lb
Phenolic Compounds	.017 lb/1000 lb	.0083 lb/1000 lb	.0032 lb/1000 lb	.0016 lb/1000 lb	0.0032 lb/1000 lb	0.0016 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24893, July 8, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (All references to lb/1000 lb are to 1000 lb of anhydrous product)	FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74					
Subpart A - Soap Manufacturing by Batch Kettle Subcategory						
BOD5	1.80 lb/1000 lb	0.60 lb/1000 lb	0.80 lb/1000 lb	0.40 lb/1000 lb	0.80 lb/1000 lb	0.40 lb/1000 lb
COD	4.50 lb/1000 lb	1.50 lb/1000 lb	2.10 lb/1000 lb	1.05 lb/1000 lb	2.10 lb/1000 lb	1.05 lb/1000 lb
TSS	1.20 lb/1000 lb	.40 lb/1000 lb	.80 lb/1000 lb	.40 lb/1000 lb	.40 lb/1000 lb	.40 lb/1000 lb
Oil & Grease	.30 lb/1000 lb	.10 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Fatty Acid Manufacturing by Fat Splitting Subcategory						
(a) Discharges from the splitting of fats to fatty acids by hydrolysis:						
BOD5	3.60 lb/1000 lb	1.20 lb/1000 lb	0.50 lb/1000 lb	0.25 lb/1000 lb	0.50 lb/1000	0.25 lb/1000 lb
COD	9.90 lb/1000 lb	3.30 lb/1000 lb	1.80 lb/1000 lb	.90 lb/1000 lb	1.80 lb/1000 lb	.90 lb/1000 lb
TSS	6.60 lb/1000 lb	2.20 lb/1000 lb	.40 lb/1000 lb	.20 lb/1000 lb	.40 lb/1000 lb	.20 lb/1000 lb
Oil & Grease	.90 lb/1000 lb	.30 lb/1000 lb	.30 lb/1000 lb	.15 lb/1000 lb	.30 lb/1000 lb	.15 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) If fatty acids are hydrogenated, the following additional allowances shall apply:						
BOD5	0.45 lb/1000 lb	0.15 lb/1000 lb	0.30 lb/1000 lb	0.15 lb/1000 lb	0.30 lb/1000 lb	0.15 lb/1000 lb
COD	.75 lb/1000 lb	.25 lb/1000 lb	.50 lb/1000 lb	.25 lb/1000 lb	.50 lb/1000 lb	.25 lb/1000 lb
TSS	.30 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
Oil & Grease	.30 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued)	FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74					
Subpart C - Soap Manufacturing by Fatty Acid Neutralization Subcategory						
BOD5	0.03 lb/1000 lb	**0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.15 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb
TSS	.06 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
Oil & Grease	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart D - Glycerine Concentration Subcategory						
BOD5	4.50 lb/1000 lb	1.50 lb/1000 lb	0.80 lb/1000 lb	0.40 lb/1000 lb	0.80 lb/1000 lb	0.40 lb/1000 lb
COD	13.50 lb/1000 lb	4.50 lb/1000 lb	2.40 lb/1000 lb	1.20 lb/1000 lb	2.40 lb/1000 lb	1.20 lb/1000 lb
TSS	.60 lb/1000 lb	.20 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
Oil & Grease	.30 lb/1000 lb	.10 lb/1000 lb	.08 lb/1000 lb	.04 lb/1000 lb	.08 lb/1000 lb	.01 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Glycerine Distillation Subcategory						
BOD5	1.50 lb/1000 lb	0.50 lb/1000 lb	0.60 lb/1000 lb	0.30 lb/1000 lb	0.60 lb/1000 lb	0.30 lb/1000 lb
COD	4.50 lb/1000 lb	1.50 lb/1000 lb	1.80 lb/1000 lb	.90 lb/1000 lb	1.80 lb/1000 lb	.90 lb/1000 lb
TSS	.60 lb/1000 lb	.20 lb/1000 lb	.08 lb/1000 lb	.04 lb/1000 lb	.08 lb/1000 lb	.04 lb/1000 lb
Oil & Grease	.30 lb/1000 lb	.10 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 17841, May 21, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued)			FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74			
Subpart F - Manufacture of Soap Flakes and Powders Subcategory						
BOD5	0.03 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.15 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb
TSS	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Oil & Grease	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart G - Manufacture of Bar Soaps Subcategory						
BOD5	1.02 lb/1000 lb	0.34 lb/1000 lb	0.40 lb/1000 lb	0.20 lb/1000 lb	0.40 lb/1000 lb	0.20 lb/1000 lb
COD	2.55 lb/1000 lb	.85 lb/1000 lb	1.20 lb/1000 lb	.60 lb/1000 lb	1.20 lb/1000 lb	.60 lb/1000 lb
TSS	1.74 lb/1000 lb	.58 lb/1000 lb	.68 lb/1000 lb	.34 lb/1000 lb	.68 lb/1000 lb	.34 lb/1000 lb
Oil & Grease	.12 lb/1000 lb	.04 lb/1000 lb	.06 lb/1000 lb	.03 lb/1000 lb	.06 lb/1000 lb	.03 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart H - Manufacture of Liquid Soaps Subcategory						
BOD5	0.03 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.15 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb
TSS	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Oil & Grease	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued)			FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74			
Subpart I - Oleum Sulfonation and Sulfation Subcategory						
BOD5	0.09 lb/1000 lb	0.02 lb/1000 lb	0.07 lb/1000 lb	0.02 lb/1000 lb	0.03 lb/1000 lb	0.01 lb/1000 lb
COD	.40 lb/1000 lb	.09 lb/1000 lb	.27 lb/1000 lb	.09 lb/1000 lb	.09 lb/1000 lb	.03 lb/1000 lb
TSS	.15 lb/1000 lb	.03 lb/1000 lb	.09 lb/1000 lb	.03 lb/1000 lb	.06 lb/1000 lb	.02 lb/1000 lb
Surfactants	.15 lb/1000 lb	.03 lb/1000 lb	.09 lb/1000 lb	.03 lb/1000 lb	.03 lb/1000 lb	.01 lb/1000 lb
Oil & Grease	.25 lb/1000 lb	.07 lb/1000 lb	.21 lb/1000 lb	.07 lb/1000 lb	.12 lb/1000 lb	.04 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart J - Air-SO3 Sulfation and Sulfonation Subcategory						
BOD5	0.90 lb/1000 lb	0.30 lb/1000 lb	0.30 lb/1000 lb	0.19 lb/1000 lb	0.18 lb/1000 lb	0.09 lb/1000 lb
COD	4.05 lb/1000 lb	1.35 lb/1000 lb	1.10 lb/1000 lb	.55 lb/1000 lb	.80 lb/1000 lb	.40 lb/1000 lb
TSS	.09 lb/1000 lb	.03 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
Surfactants	.90 lb/1000 lb	.30 lb/1000 lb	.36 lb/1000 lb	.18 lb/1000 lb	.18 lb/1000 lb	.09 lb/1000 lb
Oil & Grease	.15 lb/1000 lb	.05 lb/1000 lb	.08 lb/1000 lb	.04 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart K - SO3 Solvent and Vacuum Sulfonation Subcategory						
BOD5	0.90 lb/1000 lb	0.30 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
COD	3.05 lb/1000 lb	1.35 lb/1000 lb	.90 lb/1000 lb	.45 lb/1000 lb	.90 lb/1000 lb	.45 lb/1000 lb
TSS	.09 lb/1000 lb	.03 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued) FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74						
Subpart K - SO3 Solvent and Vacuum Sulfonation Subcategory (Continued)						
Surfactants	.90 lb/1000 lb	.30 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
Oil & Grease	.10 lb/1020 lb	.05 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart L - Sulfamic Acid Sulfation Subcategory						
BOD5	0.90 lb/1000 lb	0.30 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb
COD	4.05 lb/1000 lb	1.35 lb/1000 lb	.90 lb/1000 lb	.45 lb/1000 lb	.90 lb/1000 lb	.45 lb/1000 lb
TSS	.09 lb/1000 lb	.03 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Surfactants	.90 lb/1000 lb	.30 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
Oil & Grease	.15 lb/1000 lb	.05 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart M - Chlorosulfamic Acid Sulfation Subcategory						
BOD5	0.90 lb/1000 lb	0.30 lb/1000 lb	0.30 lb/1000 lb	0.15 lb/1000 lb	0.30 lb/1000 lb	0.15 lb/1000 lb
COD	4.05 lb/1000 lb	1.35 lb/1000 lb	1.50 lb/1000 lb	.25 lb/1000 lb	1.50 lb/1000 lb	.75 lb/1000 lb
TSS	.09 lb/1000 lb	.03 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
Surfactants	.90 lb/1000 lb	.30 lb/1000 lb	.30 lb/1000 lb	.15 lb/1000 lb	.30 lb/1000 lb	.15 lb/1000 lb
Oil & Grease	.15 lb/1000 lb	.05 lb/1000 lb	.06 lb/1000 lb	.03 lb/1000 lb	.06 lb/1000 lb	.03 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued) FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74						
Subpart N - Neutralization of Sulfuric Acid Esters and Sulfunic Acids Subcategory						
BOD5	0.03 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.15 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.06 lb/1000 lb	.04 lb/1000 lb
TSS	.09 lb/1000 lb	.03 lb/1000 lb	.06 lb/1000 lb	.03 lb/1000 lb	.06 lb/1000 lb	.03 lb/1000 lb
Surfactants	.06 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
Oil & Grease	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart O - Manufacture of Spray Dried Detergents Subcategory						
(a) For normal operation of spray drying towers:						
BOD5	0.03 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.15 lb/1000 lb	.05 lb/1000 lb	.08 lb/1000 lb	.04 lb/1000 lb	.08 lb/1000 lb	.04 lb/1000 lb
TSS	.03 lb/1000 lb	.01 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
Surfactants	.06 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
Oil & Grease	.015 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued) FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74						
Subpart D - Manufacture of Spray Dried Detergents Subcategory (Continued)						
(b) For air quality restricted operation of a spray drying tower, but only when a high rate of wet scrubbing is in operation which produces more waste water than can be recycled to process, the following values pertain:						
BOD5	0.24 lb/1000 lb	0.08 lb/1000 lb	0.12 lb/1000 lb	0.04 lb/1000 lb	0.12 lb/1000 lb	0.04 lb/1000 lb
COD	1.05 lb/1000 lb	.35 lb/1000 lb	.50 lb/1000 lb	.25 lb/1000 lb	.50 lb/1000 lb	.25 lb/1000 lb
TSS	.30 lb/1000 lb	.10 lb/1000 lb	.14 lb/1000 lb	.07 lb/1000 lb	.14 lb/1000 lb	.07 lb/1000 lb
Surfactants	.45 lb/1000 lb	.15 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
Oil & Grease	.09 lb/1000 lb	.03 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(c) For fast turnaround operation of a spray tower, the following values pertain: The maximum for any one day when the number of turnarounds exceeds six in any particular thirty consecutive day period shall be the sum of the appropriate value below and that from (a) or (b) of this section; and the average of daily values for thirty consecutive days shall be the value shown below multiplied by the number of turnarounds in excess of six and prorated to thirty days plus the appropriate value from (a) or (b) of this section.						
BOD5	0.02 lb/1000 lb		0.02 lb/1000 lb		0.02 lb/1000 lb	
COD	.09 lb/1000 lb		.07 lb/1000 lb		.07 lb/1000 lb	
TSS	.02 lb/1000 lb		.02 lb/1000 lb		.02 lb/1000 lb	
Surfactants	.03 lb/1000 lb		.02 lb/1000 lb		.02 lb/1000 lb	
Oil & Grease	.005 lb/1000 lb		.005 lb/1000 lb		.005 lb/1000 lb	
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued) FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74						
Subpart P - Manufacture of Liquid Detergents Subcategory						
(a) For normal liquid detergent operations the following values pertain:						
BOD5	0.60 lb/1000 lb	0.20 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb	0.10 lb/1000 lb	0.05 lb/1000 lb
COD	**1.80 lb/1000 lb	.60 lb/1000 lb	.44 lb/1000 lb	.22 lb/1000 lb	.44 lb/1000 lb	.22 lb/1000 lb
TSS	.015 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb
Surfactants	.39 lb/1000 lb	.13 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb
Oil & Grease	.015 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) For fast turnaround operation of automated fill lines, the following values pertain: the maximum for any one day when the number of turnarounds exceeds eight in any thirty consecutive day period shall be the sum of the appropriate value below and that from (a) of this section; and the average of daily values for thirty consecutive days shall be the value shown below multiplied by the number of turnarounds in excess of eight and prorated to thirty days plus the appropriate value from (a) of this section.						
BOD5	0.05 lb/1000 lb		0.02 lb/1000 lb		0.02 lb/1000 lb	
COD	.15 lb/1000 lb		.07 lb/1000 lb		.07 lb/1000 lb	
TSS	.002 lb/1000 lb		.002 lb/1000 lb		.002 lb/1000 lb	
Surfactants	.04 lb/1000 lb		.02 lb/1000 lb		.02 lb/1000 lb	
Oil & Grease	.002 lb/1000 lb		.002 lb/1000 lb		.002 lb/1000 lb	
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 17841, May 21, 1974.

Parameter	PSES Daily	PSES 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued)	FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74					
Subpart Q - Manufacture of Detergents by Dry Blending Subcategory						
BOD5	0.03 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.21 lb/1000 lb	.07 lb/1000 lb	.14 lb/1000 lb	.07 lb/1000 lb	.14 lb/1000 lb	.07 lb/1000 lb
TSS	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Surfactants	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Oil & Grease	.015 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb	.01 lb/1000 lb	.005 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart R - Manufacture of Drum Dried Detergents Subcategory						
BOD5	0.03 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb	0.02 lb/1000 lb	0.01 lb/1000 lb
COD	.15 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb	.10 lb/1000 lb	.05 lb/1000 lb
TSS	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Surfactants	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
Oil & Grease	.03 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb	.02 lb/1000 lb	.01 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 417 - SOAP AND DETERGENT (Continued)			FINAL REGULATIONS, PUBLISHED 4/12/74, EFFECTIVE 6/11/74			
Subpart S - Manufacture of Detergent Bars and Cakes Subcategory						
BOD5	2.10 lb/1000 lb	0.70 lb/1000 lb	0.60 lb/1000 lb	0.30 lb/1000 lb	0.60 lb/1000 lb	0.30 lb/1000 lb
COD	9.90 lb/1000 lb	3.30 lb/1000 lb	2.70 lb/1000 lb	1.35 lb/1000 lb	2.70 lb/1000 lb	1.35 lb/1000 lb
TSS	.60 lb/1000 lb	.30 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb	.20 lb/1000 lb	.10 lb/1000 lb
Surfactants	1.50 lb/1000 lb	.50 lb/1000 lb	.40 lb/1000 lb	.20 lb/1000 lb	.40 lb/1000 lb	.20 lb/1000 lb
Oil & Grease	.06 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb	.04 lb/1000 lb	.02 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 418 - FERTILIZER MANUFACTURING	FINAL REGULATIONS, PUBLISHED 4/8/74, EFFECTIVE 6/7/74 (All references to lb/1000 lb are to 1000 lb of product)					
Subpart A - Phosphate Subcategory						
	(a) Subject to the provisions of paragraphs (b), (c), and (d) of this section, there shall be no discharge of process waste water pollutants into navigable waters.		(a) Subject to the provisions of paragraph (b) of this section there shall be no discharge of process waste water pollutants into navigable waters.		(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants into navigable waters.	
	(b) A process waste water impoundment which is designed, constructed and operated so as to contain the precipitation from the 10 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration, for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 10 year, 24 hour rainfall event, when such event occurs.		(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration, for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.		(b) A process waste water impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25 year, 24 hour rainfall event as established by the National Climatic Center, National Oceanic Atmospheric Administration, for the area in which such impoundment is located may discharge that volume of process waste water which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25 year, 24 hour rainfall event, when such event occurs.	
	(c) During any calendar month there may be discharged from a process waste water impoundment either a volume of process waste water equal to the difference between the precipitation for that month that falls within the impoundment and the evaporation within the impoundment for that month, or, if greater, a volume of process waste water equal to the difference between the mean precipitation for that month that falls within the impoundment and the mean evaporation for that month as established by the National Climatic Center, National Oceanic and Atmospheric Administration, for the area in which such impoundment is located (or as otherwise determined if no monthly data have been established by the National Climatic Center).					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 418 - FERTILIZER MANUFACTURING (Continued)			FINAL REGULATIONS, PUBLISHED 4/8/74, EFFECTIVE 6/7/74			
Subpart A - Phosphate Subcategory (Continued)						
(d) Any process waste water discharged pursuant to paragraph (c) of this section shall comply with each of the following requirements:						
Total Phosphorus	70 ppm	35 ppm				
Fluoride	30 ppm	15 ppm				
TSS	50 ppm	25 ppm				
pH	8.0 - 9.5					
Subpart B - Ammonia Subcategory						
Ammonia	0.125 lb/1000 lb	0.0625 lb/1000 lb	0.05 lb/1000 lb	0.025 lb/1000 lb	0.11 lb/1000 lb	0.055 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart C - Urea Subcategory						
(a) Limitations for maximum permissible discharge for urea manufacturing operations in which urea is not prilled:						
Ammonia	0.075 lb/1000 lb	0.0375 lb/1000 lb	0.03 lb/1000 lb	0.015 lb/1000 lb	0.065 lb/1000 lb	0.0325 lb/1000 lb
Organic Nitrogen	**.44 lb/1000 lb	**0.175 lb/1000 lb	.05 lb/1000 lb	.025 lb/1000 lb	**.24 lb/1000 lb	**.12 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**Corrected per 39 FR 24490, July 2, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 418 - FERTILIZER MANUFACTURING (Continued)	FINAL REGULATIONS, PUBLISHED 4/8/74, EFFECTIVE 6/7/74					
Subpart C - Urea Subcategory (Continued)						
(b) Limitations for maximum permissible discharge for urea manufacturing operations in which urea is prilled:						
Ammonia	0.1 lb/1000 lb	0.05 lb/1000 lb	0.03 lb/1000 lb	0.015 lb/1000 lb	0.065 lb/1000 lb	0.0325 lb/1000 lb
Organic Nitrogen	**1.25 lb/1000 lb	**.5 lb/1000 lb	.075 lb/1000 lb	.0375 lb/1000 lb	**.7 lb/1000 lb	**.35 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart D - Ammonium Nitrate Subcategory						
(a) Limitations for maximum permissible discharge for ammonium nitrate manufacturing operations in which ammonium nitrate is produced as an aqueous solution:						
Ammonia	0.075 lb/1000 lb	0.0375 lb/1000 lb	0.015 lb/1000 lb	0.0075 lb/1000 lb	0.05 lb/1000 lb	0.025 lb/1000 lb
Nitrate	.1 lb/1000 lb	.05 lb/1000 lb	.025 lb/1000 lb	.0125 lb/1000 lb	.025 lb/1000 lb	.0125 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
(b) Limitations for maximum permissible discharge for ammonium nitrate manufacturing operations in which ammonium nitrate is prilled or granulated:						
Ammonia	0.2 lb/1000 lb	0.1 lb/1000 lb	0.015 lb/1000 lb	0.0075 lb/1000 lb	0.1 lb/1000 lb	0.25 lb/1000 lb
Nitrate	.22 lb/1000 lb	.11 lb/1000 lb	.025 lb/1000 lb	.0125 lb/1000 lb	.05 lb/1000 lb	.025 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Nitric Acid Subcategory						
	There shall be no discharge of process waste water pollutants into navigable waters.		There shall be no discharge of process waste water pollutants into navigable waters.		There shall be no discharge of process waste water pollutants into navigable waters.	

**Corrected per 39 FR 24690, July 2, 1974.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 419 - PETROLEUM REFINING	FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74					
Subpart A - Topping Subcategory						
(a)						
BOD5	8.0 lb/1000 bbl feedstock	4.25 lb/1000 bbl feedstock	0.92 lb/1000 bbl feedstock	0.75 lb/1000 bbl feedstock	4.2 lb/1000 bbl feedstock	2.2 lb/1000 bbl feedstock
TSS	4.9 lb/1000 bbl feedstock	2.9 lb/1000 bbl feedstock	.88 lb/1000 bbl feedstock	.75 lb/1000 bbl feedstock	2.6 lb/1000 bbl feedstock	1.5 lb/1000 bbl feedstock
COD**	41.2 lb/1000 bbl feedstock	21.3 lb/1000 bbl feedstock	3.5 lb/1000 bbl feedstock	2.8 lb/1000 bbl feedstock	21.7 lb/1000 bbl feedstock	11.2 lb/1000 bbl feedstock
Oil & Grease	2.5 lb/1000 bbl feedstock	1.3 lb/1000 bbl feedstock	.18 lb/1000 bbl feedstock	.14 lb/1000 bbl feedstock	1.3 lb/1000 bbl feedstock	.70 lb/1000 bbl feedstock
Phenolic Compounds	.060 lb/1000 bbl feedstock	.027 lb/1000 bbl feedstock	.0043 lb/1000 bbl feedstock	.0031 lb/1000 bbl feedstock	.031 lb/1000 bbl feedstock	.016 lb/1000 bbl feedstock
Ammonia as N	.99 lb/1000 bbl feedstock	.45 lb/1000 bbl feedstock	.24 lb/1000 bbl feedstock	.18 lb/1000 bbl feedstock	1.0 lb/1000 bbl feedstock	.45 lb/1000 bbl feedstock
Sulfide	.053 lb/1000 bbl feedstock	.024 lb/1000 bbl feedstock	.019 lb/1000 bbl feedstock	.015 lb/1000 bbl feedstock	.027 lb/1000 bbl feedstock	.012 lb/1000 bbl feedstock
Total Chromium	.122 lb/1000 bbl feedstock	.071 lb/1000 bbl feedstock	.044 lb/1000 bbl feedstock	.037 lb/1000 bbl feedstock	.064 lb/1000 bbl feedstock	.037 lb/1000 bbl feedstock
Hexavalent Chromium	.0025 lb/1000 bbl feedstock	.0011 lb/1000 bbl feedstock	.00097 lb/1000 bbl feedstock	.00062 lb/1000 bbl feedstock	.0013 lb/1000 bbl feedstock	.00062 lb/1000 bbl feedstock
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1000 mg/l (1000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD. Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD5. If in the judgment of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD5.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 419 - PETROLEUM REFINING (Continued) FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74

Subpart A - Topping Subcategory (Continued)

(b) The limits set forth in (a) are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days. (Applies to BPT, BAT and New Sources)

(1) Size factor.

1,000 barrels feedstock per stream day	Size factor
0 to 49.9	1.02
50 to 99.9	1.21
100 to 149.9	1.44
150 or greater	1.57

(2) Process factor

Process configuration	Process factor
1.0 to 3.99	0.60
4.0 to 6.99	1.00
7.0 to 9.99	1.66
10.0 to 12.99	2.77
13.0 to 15.0 or greater	4.09

(c) The following allocations apply in addition to the discharge allowed by (b).

(1) RUNOFF. The allocation allowed for storm runoff flow, as kg/cu m (lb/m gal), shall be based solely on that storm flow (process area runoff) which is treated in the main treatment system. All additional storm runoff (from tank fields and non-process areas), that has been segregated from the main waste stream for discharge, shall not exceed a concentration of 35 mg/l of TOC or 15 mg/l of oil and grease when discharged.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 419 - PETROLEUM REFINING (Continued)	FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74					
Subpart A - Topping Subcategory (Continued)						
BOD5	0.40 lb/1000 gal flow	0.21 lb/1000 gal flow	0.088 lb/1000 gal flow	0.071 lb/1000 gal flow	0.40 lb/1000 gal flow	0.21 lb/1000 gal flow
TSS	.24 lb/1000 gal flow	.14 lb/1000 gal flow	.084 lb/1000 gal flow	.071 lb/1000 gal flow	.24 lb/1000 gal flow	.14 lb/1000 gal flow
COD**	3.1 lb/1000 gal flow	1.6 lb/1000 gal flow	.24 lb/1000 gal flow	.19 lb/1000 gal flow	3.1 lb/1000 gal flow	1.6 lb/1000 gal flow
Oil & Grease	.126 lb/1000 gal flow	.067 lb/1000 gal flow	.018 lb/1000 gal flow	.014 lb/1000 gal flow	.126 lb/1000 gal flow	.067 lb/1000 gal flow
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

(2) BALLAST. The allocation allowed for ballast water flow, as kg/cu m (lb/Mgal), shall be based on those ballast waters treated at the refinery.

BOD5	0.40 lb/1000 gal flow	0.21 lb/1000 gal flow	0.088 lb/1000 gal flow	0.071 lb/1000 gal flow	0.40 lb/1000 gal flow	0.21 lb/1000 gal flow
TSS	.24 lb/1000 gal flow	.14 lb/1000 gal flow	.084 lb/1000 gal flow	.071 lb/1000 gal flow	.24 lb/1000 gal flow	.14 lb/1000 gal flow
COD**	3.9 lb/1000 fal flow	2.0 lb/1000 gal flow	.32 lb/1000 gal flow	.26 lb/1000 gal flow	3.9 lb/1000 gal flow	2.0 lb/1000 gal flow
Oil & Grease	.126 lb/1000 gal flow	.067 lb/1000 gal flow	.018 lb/1000 gal flow	.014 lb/1000 gal flow	.126 lb/1000 gal flow	.067 lb/1000 gal flow
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

(d) The quantity and quality of pollutants or pollutant properties controlled by this section, attributable to once-through cooling water, are excluded from the discharge allowed by (b) of this section. Once-through cooling water may be discharged with a total organic carbon concentration not to exceed 5 mg/l.

**In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1000 mg/l (1000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD. Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD5. If in the judgment of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD5.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 419 - PETROLEUM REFINING (Continued)			FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74			
Subpart B - Cracking Subcategory						
(a)						
BOD5	9.9 lb/1000 bbl feedstock	5.5 lb/1000 bbl feedstock	1.2 lb/1000 bbl feedstock	0.99 lb/1000 bbl feedstock	5.8 lb/1000 bbl feedstock	3.1 lb/1000 bbl feedstock
TSS	6.1 lb/1000 bbl feedstock	3.6 lb/1000 bbl feedstock	1.2 lb/1000 bbl feedstock	0.99 lb/1000 bbl feedstock	3.5 lb/1000 bbl feedstock	2.0 lb/1000 bbl feedstock
COD**	74 lb/1000 bbl feedstock	38.4 lb/1000 bbl feedstock	6.8 lb/1000 bbl feedstock	5.4 lb/1000 bbl feedstock	41.5 lb/1000 bbl feedstock	21.0 lb/1000 bbl feedstock
Oil & Grease	3.0 lb/1000 bbl feedstock	1.6 lb/1000 bbl feedstock	.24 lb/1000 bbl feedstock	.19 lb/1000 bbl feedstock	1.7 lb/1000 bbl feedstock	.93 lb/1000 bbl feedstock
Phenolic Compounds	.074 lb/1000 bbl feedstock	.036 lb/1000 bbl feedstock	.0055 lb/1000 bbl feedstock	.0039 lb/1000 bbl feedstock	.042 lb/1000 bbl feedstock	.020 lb/1000 bbl feedstock
Ammonia as N	6.6 lb/1000 bbl feedstock	3.0 lb/1000 bbl feedstock	1.6 lb/1000 bbl feedstock	1.2 lb/1000 bbl feedstock	6.6 .o/1000 bbl feedstock	3.0 lb/1000 bbl feedstock
Sulfide	.065 lb/1000 bbl feedstock	.029 lb/1000 bbl feedstock	.026 lb/1000 bbl feedstock	.017 lb/1000 bbl feedstock	.037 lb/1000 bbl feedstock	.017 lb/1000 bbl feedstock
Total Chromium	.15 lb/1000 bbl feedstock	.080 lb/1000 bbl feedstock	.050 lb/1000 bbl feedstock	.049 lb/1000 bbl feedstock	.084 lb/1000 bbl feedstock	.049 lb/1000 bbl feedstock
Hexavalent Chromium	.0031 lb/1000 bbl feedstock	.0014 lb/1000 bbl feedstock	.0013 lb/1000 bbl feedstock	.0008 lb/1000 bbl feedstock	.0018 lb/1000 bbl feedstock	.00081 lb/1000 bbl feedstock
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1,000 mg/l (1,000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD. Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD5. If in the judgement of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD5.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 419 - PETROLEUM REFINING (Continued) FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74

Subpart B - Cracking Subcategory (Continued)

(b) The limits set forth in (a) are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days. (Applies to BPT, BAT and New Sources)

(1) Size factor.

1,000 barrels feedstock per stream day	Size factor
0 to 34.9	0.89
35 to 74.9	1.00
75 to 109.9	1.14
110 to 149.9	1.31
150 or greater	1.41

(2) Process factor

Process configuration	Process factor
1.5 to 3.49	0.58
3.50 to 5.49	0.81
5.50 to 7.49	1.13
7.50 to 9.49	1.60
9.50 to 10.50 or greater	1.87

(c) The provisions of Subpart A (c) (1) and (2) apply to discharges of process waste water pollutants attributable to storm water runoff and ballast water by a point source subject to the provisions of this subpart.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by (b) of this section. Once-through cooling water may be discharged a total organic carbon concentration not to exceed 5 mg/l.

Parameter	*BPT Daily	30 Day	BAT Daily	30 Day	New Sources Daily	30 Day
PART 419 - PETROLEUM REFINING (Continued)			FINAL REGULATION, PUBLISHED 5/9/74, EFFECTIVE 5/12/74			
Subpart C - Petrochemical Subcategory						
(a)						
BOD5	12.1 lb/1000 bbl feedstock	6.5 lb/1000 bbl feedstock	1.7 lb/1000 bbl feedstock	1.7 lb/1000 bbl feedstock	7.7 lb/1000 bbl feedstock	4.1 lb/1000 bbl feedstock
TSS	7.3 lb/1000 bbl feedstock	4.25 lb/1000 bbl feedstock	1.6 lb/1000 bbl feedstock	1.3 lb/1000 bbl feedstock	4.6 lb/1000 bbl feedstock	2.7 lb/1000 bbl feedstock
COD**	74 lb/1000 bbl feedstock	38.4 lb/1000 bbl feedstock	7.6 lb/1000 bbl feedstock	6.1 lb/1000 bbl feedstock	47 lb/1000 bbl feedstock	24 lb/1000 bbl feedstock
Oil & Grease	3.9 lb/1000 bbl feedstock	2.1 lb/1000 bbl feedstock	.32 lb/1000 bbl feedstock	.26 lb/1000 bbl feedstock	2.4 lb/1000 bbl feedstock	1.3 lb/1000 bbl feedstock
Phenolic Compounds	.068 lb/1000 bbl feedstock	.0425 lb/1000 bbl feedstock	.0077 lb/1000 bbl feedstock	.0054 lb/1000 bbl feedstock	.056 lb/1000 bbl feedstock	.027 lb/1000 bbl feedstock
Ammonia as N	8.25 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock	2.0 lb/1000 bbl feedstock	1.5 lb/1000 bbl feedstock	8.3 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock
Sulfide	.076 lb/1000 bbl feedstock	.035 lb/1000 bbl feedstock	.035 lb/1000 bbl feedstock	.022 lb/1000 bbl feedstock	.050 lb/1000 bbl feedstock	.022 lb/1000 bbl feedstock
Total Chromium	.183 lb/1000 bbl feedstock	.107 lb/1000 bbl feedstock	.080 lb/1000 bbl feedstock	.068 lb/1000 bbl feedstock	.116 lb/1000 bbl feedstock	.068 lb/1000 bbl feedstock
Hexavalent Chromium	.0040 lb/1000 bbl feedstock	.0018 lb/1000 bbl feedstock	.0017 lb/1000 bbl feedstock	.0011 lb/1000 bbl feedstock	.0024 lb/1000 bbl feedstock	.0011 lb/1000 bbl feedstock
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1,000 mg/l (1,000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD. Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD5. If in the judgement of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD5.

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 419 - PETROLEUM REFINING (Continued) FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74

Subpart C - Petrochemical Subcategory (Continued)

(b) The limits set forth in (a) are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days. (Applies to BPT, BAT and New Sources)

(1) Size factor.

1,000 barrels feedstock per stream day	Size factor
0 to 49.9	0.73
50 to 99.9	.87
100 to 149.9	1.00
150 or greater	1.13

(2) Process factor

Process configuration	Process factor
3.25 to 4.74	0.67
4.75 to 6.74	.91
6.75 to 8.74	1.27
8.75 to 10.25 or greater	1.84

(c) The provisions of Subpart A (c) (1) and (2) apply to discharges of process waste water pollutants attributable to storm water runoff and ballast water by a point source subject to the provisions of this subpart.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by (b) of this section. Once-through cooling water may be discharged with a total organic carbon concentration not to exceed 5 mg/l.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 419 - PETROLEUM REFINING (Continued)		FINAL REGULATIONS, PUBLISHED 5/8/74, EFFECTIVE 5/12/74				
Subpart B - Lube Subcategory						
(a)						
BOD5	17.9 lb/1000 bbl feedstock	9.1 lb/1000 bbl feedstock	2.7 lb/1000 bbl feedstock	2.2 lb/1000 bbl feedstock	12.2 lb/1000 bbl feedstock	6.5 lb/1000 bbl feedstock
TSS	11.0 lb/1000 bbl feedstock	6.5 lb/1000 bbl feedstock	2.6 lb/1000 bbl feedstock	2.2 lb/1000 bbl feedstock	7.3 lb/1000 bbl feedstock	4.3 lb/1000 bbl feedstock
COD**	127 lb/1000 bbl feedstock	66 lb/1000 bbl feedstock	13.8 lb/1000 bbl feedstock	11.0 lb/1000 bbl feedstock	87.0 lb/1000 bbl feedstock	45.0 lb/1000 bbl feedstock
Oil & Grease	5.7 lb/1000 bbl feedstock	3.0 lb/1000 bbl feedstock	.50 lb/1000 bbl feedstock	.40 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock	2.0 lb/1000 bbl feedstock
Phenolic Compounds	.133 lb/1000 bbl feedstock	.065 lb/1000 bbl feedstock	.012 lb/1000 bbl feedstock	.0087 lb/1000 bbl feedstock	.088 lb/1000 bbl feedstock	.043 lb/1000 bbl feedstock
Ammonia as N	8.3 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock	2.0 lb/1000 bbl feedstock	1.5 lb/1000 bbl feedstock	8.3 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock
Sulfide	.118 lb/1000 bbl feedstock	.053 lb/1000 bbl feedstock	.055 lb/1000 bbl feedstock	.035 lb/1000 bbl feedstock	.078 lb/1000 bbl feedstock	.035 lb/1000 bbl feedstock
Total Chromium	.273 lb/1000 bbl feedstock	.160 lb/1000 bbl feedstock	.13 lb/1000 bbl feedstock	.11 lb/1000 bbl feedstock	.180 lb/1000 bbl feedstock	.105 lb/1000 bbl feedstock
Hexavalent Chromium	.0059 lb/1000 bbl feedstock	.0027 lb/1000 bbl feedstock	.0029 lb/1000 bbl feedstock	.0018 lb/1000 bbl feedstock	.0056 lb/1000 bbl feedstock	.0018 lb/1000 bbl feedstock
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1,000 mg/l (1,000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD. Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD5. If in the judgement of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD5.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 419 - PETROLEUM REFINING (Continued)

FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74

Subpart D - Lube Subcategory (Continued)

(b) The limits set forth in (a) of this section are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days. (Applies to BPT, BAT and New Sources)

(1) Size factor

1,000 barrels of feedstock per stream day	Size factor
30 to 69.9	0.71
70 to 109.9	0.81
110 to 149.9	0.93
150 to 199.9	1.09
200 or greater	1.19

(2) Process factor

Process configuration	Process factor
6.0 or less to 7.99	0.88
8.0 to 9.99	1.23
10.0 to 11.99	1.74
12.0 to 14.0 or greater	2.44

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 419 - PETROLEUM REFINING (Continued)		FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/74				

Subpart D - Lube Subcategory (Continued)

(3) Example of the application of the above factors.

Calculation of the process configuration

Process Category	Processes included	Weighting factor
Crude	Atm. crude distillation Vacuum crude distillation Desalting	1
Cracking and Coking	Fluid cat. cracking Vis-breaking	6
	Thermal cracking. Moving bed cat. cracking. Hydrocracking. Fluid coking. Delayed coking.	
Lube	Further defined in the development document.	13
Asphalt	Asphalt production Asphalt oxidation Asphalt emulsifying.	12

(c) The provisions of Subpart A (c) (1) and (2) apply to discharges of process waste water pollutants attributable to storm water runoff and ballast water by a point source subject to the provisions of this subpart.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by (b) of this section. Once-through cooling water may be discharged with a total organic carbon concentration not to exceed 5 mg/l.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 419 - PETROLEUM REFINING (Continued)			FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/12/78			
Subpart E - Integrated Subcategory						
BOD5 (a)	19.2 lb/1000 bbl feedstock	10.2 lb/1000 bbl feedstock	3.2 lb/1000 bbl feedstock	2.6 lb/1000 bbl feedstock	14.7 lb/1000 bbl feedstock	7.8 lb/1000 bbl feedstock
TSS	11.6 lb/1000 bbl feedstock	6.8 lb/1000 bbl feedstock	3.0 lb/1000 bbl feedstock	2.6 lb/1000 bbl feedstock	8.7 lb/1000 bbl feedstock	5.1 lb/1000 bbl feedstock
COD**	136.0 lb/1000 bbl feedstock	70.0 lb/1000 bbl feedstock	16.8 lb/1000 bbl feedstock	13.4 lb/1000 bbl feedstock	104.0 lb/1000 bbl feedstock	54.0 lb/1000 bbl feedstock
Oil & Grease	6.0 lb/1000 bbl feedstock	3.2 lb/1000 bbl feedstock	.60 lb/1000 bbl feedstock	.48 lb/1000 bbl feedstock	4.5 lb/1000 bbl feedstock	2.4 lb/1000 bbl feedstock
Phenolic Compounds	.14 lb/1000 bbl feedstock	.068 lb/1000 bbl feedstock	.015 lb/1000 bbl feedstock	.010 lb/1000 bbl feedstock	.105 lb/1000 bbl feedstock	.051 lb/1000 bbl feedstock
Ammonia as N	8.3 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock	2.0 lb/1000 bbl feedstock	1.5 lb/1000 bbl feedstock	8.3 lb/1000 bbl feedstock	3.8 lb/1000 bbl feedstock
Sulfide	.124 lb/1000 bbl feedstock	.056 lb/1000 bbl feedstock	.066 lb/1000 bbl feedstock	.042 lb/1000 bbl feedstock	.093 lb/1000 bbl feedstock	.042 lb/1000 bbl feedstock
Total Chromium	.29 lb/1000 bbl feedstock	.17 lb/1000 bbl feedstock	.15 lb/1000 bbl feedstock	.13 lb/1000 bbl feedstock	.220 lb/1000 bbl feedstock	.13 lb/1000 bbl feedstock
Hexavalent Chromium	.0062 lb/1000 bbl feedstock	.0028 lb/1000 bbl feedstock	.0033 lb/1000 bbl feedstock	.0021 lb/1000 bbl feedstock	.0047 lb/1000 bbl feedstock	.0021 lb/1000 bbl feedstock
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

**In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1,000 mg/l (1,000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD. Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD5. If in the judgment of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD5.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

Subpart E - Integrate' Subcategory (Continued)

(b) The limits set forth in (a) of this section are to be multiplied by the following factors to calculate the maximum for any one day and the maximum average of daily values for thirty consecutive days. (Applies to BPT, BAT and New Sources)

(1) Size factor

1,000 barrels of feedstock per stream day	Size factor
70 to 144.9	0.69
145 to 219.9	0.89
220 or greater	1.02

(2) Process factor

Process configuration	Process factor
6.0 or less to 7.49	0.78
7.5 to 8.99	1.00
9.0 to 10.5 or greater	1.30

(c) The provisions of Subpart A (c) (1) and (2) apply to discharges of process waste water pollutants attributable to storm water runoff and ballast water by a point source subject to the provisions of this subpart.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by (b) of this section. Once-through cooling water may be discharged with a total organic concentration not to exceed 5 mg/l.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
Part 420 - IRON AND STEEL MANUFACTURING: FINAL REGULATIONS, PUBLISHED 6/28/74, EFFECTIVE 6/28/74 (All reference: to lb/1000 lb are to 1000 lb of product)						
Subpart A - By-Product Coke Subcategory						
(a) Subject to the provisions of (b) and (c) of this section, the effluent quality required is as set forth below:						
Ammonia	.2736 lb/1000 lb	.0912 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb
Cyanide	.0657 lb/1000 lb	.0219 lb/1000 lb				
Cyanide A			.0003 lb/1000 lb	.0001 lb/1000 lb	.0003 lb/1000 lb	.0001 lb/1000 lb
Oil & Grease	.0327 lb/1000 lb	.0109 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb
Phenol	.0045 lb/1000 lb	.0015 lb/1000 lb	.0006 lb/1000 lb	.0002 lb/1000 lb	.0006 lb/1000 lb	.0002 lb/1000 lb
TSS	.1095 lb/1000 lb	.0365 lb/1000 lb	.0312 lb/1000 lb	.0104 lb/1000 lb	.0312 lb/1000 lb	.0104 lb/1000 lb
Sulfide			.0003 lb/1000 lb	.0001 lb/1000 lb	.0003 lb/1000 lb	.0001 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

(b) For coke plants utilizing desulfurization units, the limitations specified may be exceeded up to 15 percent by those facilities equipped with gas desulfurization units to the extent that such measured discharge is necessary by reason of the increased effluent volume generated by these facilities.

(b) For coke plants utilizing desulfurization units, the limitations specified may be exceeded up to 25 percent by those facilities equipped with gas desulfurization units to the extent that such measured discharge is necessary by reason of the increased effluent volume generated by these facilities.

(b) For coke plants utilizing desulfurization units, the limitations specified may be exceeded up to 25 percent by those facilities equipped with gas desulfurization units to the extent that such measured discharge is necessary by reason of the increased effluent volume generated by these facilities.

(c) For coke plants utilizing the indirect ammonia recovery process, the limitations specified in (a) of this section may be exceeded up to 30 percent by those facilities recovering ammonia by this technique, to the extent that such measured discharge is necessary by reason of the increased effluent volume generated by this process.

(c) For coke plants utilizing the indirect ammonia recovery process, the limitations specified in (a) of this section may be exceeded up to 70 percent by those facilities recovering ammonia by this technique, to the extent that such measured discharge is necessary by reason of the increased effluent volume generated by this process.

(c) For coke plants utilizing the indirect ammonia recovery process, the limitations specified in (a) of this section may be exceeded up to 70 percent by those facilities recovering ammonia by this technique, to the extent that such measured discharge is necessary by reason of the increased effluent volume generated by this process.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
Part 420 - IRON AND STEEL MANUFACTURING			FINAL REGULATIONS, PUBLISHED 6/28/74, EFFECTIVE 6/28/74			
Subpart B - Beehive Coke Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart C - Sintering Subcategory						
Oil & Grease	.0063 lb/1000 lb	.0021 lb/1000 lb	.0063 lb/1000 lb	.0021 lb/1000 lb	.0063 lb/1000 lb	.0021 lb/1000 lb
Sulfide			.00018 lb/1000 lb	.00006 lb/1000 lb	.00018 lb/1000 lb	.00006 lb/1000 lb
Fluoride			.0126 lb/1000 lb	.0042 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb
TSS	.0312 lb/1000 lb	.0104 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart D - Blast Furnace (Iron) Subcategory						
TSS	.0780 lb/1000 lb	.0260 lb/1000 lb	.0390 lb/1000 lb	.0130 lb/1000 lb	.0390 lb/1000 lb	.0130 lb/1000 lb
Cyanide	.0234 lb/1000 lb	.0078 lb/1000 lb				
Cyanide A			.0004 lb/1000 lb	.00013 lb/1000 lb	.0004 lb/1000 lb	.00013 lb/1000 lb
Phenol	.0063 lb/1000 lb	.0021 lb/1000 lb	.0008 lb/1000 lb	.00026 lb/1000 lb	.0008 lb/1000 lb	.00026 lb/1000 lb
Ammonia	.1953 lb/1000 lb	.0651 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
Sulfide			.0005 lb/1000 lb	.00016 lb/1000 lb	.0005 lb/1000 lb	.00016 lb/1000 lb
Fluoride			.0312 lb/1000 lb	.0104 lb/1000 lb	.0312 lb/1000 lb	.0104 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
Part 420 - IRON AND STEEL MANUFACTURING (Continued)			FINAL REGULATIONS, PUBLISHED 6/28/74, EFFECTIVE 6/28/74			
Subpart E - Blast Furnace (Ferromanganese) Subcategory						
TSS	.3129 lb/1000 lb	.1043 lb/1000 lb	.0780 lb/1000 lb	.0260 lb/1000 lb	.0780 lb/1000 lb	.0260 lb/1000 lb
Cyanide	.4689 lb/1000 lb	.1563 lb/1000 lb				
Cyanide A			.0008 lb/1000 lb	.00026 lb/1000 lb	.0008 lb/1000 lb	.00026 lb/1000 lb
Phenol	.0624 lb/1000 lb	.0208 lb/1000 lb	.0016 lb/1000 lb	.00052 lb/1000 lb	.0016 lb/1000 lb	.00052 lb/1000 lb
Ammonia	1.5636 lb/1000 lb	.5212 lb/1000 lb	.0312 lb/1000 lb	.0104 lb/1000 lb	.0312 lb/1000 lb	.0104 lb/1000 lb
Sulfide			.0009 lb/1000 lb	.0003 lb/1000 lb	.0009 lb/1000 lb	.0003 lb/1000 lb
Manganese			.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart F - Basic Oxygen Furnace (Semi-wet Air Pollution Control Methods) Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart G - Basic Oxygen Furnace (Wet Air Pollution Control Methods) Subcategory						
TSS	.0312 lb/1000 lb	.0104 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
Fluoride			.0126 lb/1000 lb	.0042 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
Part 420 - IRON AND STEEL MANUFACTURING (Continued)			FINAL REGULATIONS, PUBLISHED 6/28/74, EFFECTIVE 6/28/74			
Subpart H - Open Hearth Furnace Subcategory						
TSS	.0312 lb/1000 lb	.0104 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
Fluoride			.0126 lb/1000 lb	.0042 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb
Nitrate			.0282 lb/1000 lb	.0094 lb/1000 lb		
Zinc			.0030 lb/1000 lb	.0010 lb/1000 lb	.0030 lb/1000 lb	.0010 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart I - Electric Arc Furnace (Semi-wet Air Pollution Control Methods) Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart J - Electric Arc Furnace (Wet Air Pollution Control Methods) Subcategory						
TSS	.0312 lb/1000 lb	.0104 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
Fluoride			.0126 lb/1000 lb	.0042 lb/1000 lb	.0126 lb/1000 lb	.0042 lb/1000 lb
Zinc			.0030 lb/1000 lb	.0010 lb/1000 lb	.0030 lb/1000 lb	.0010 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart K - Vacuum Degassing Subcategory						
TSS	.0156 lb/1000 lb	.0052 lb/1000 lb	.0078 lb/1000 lb	.0026 lb/1000 lb	.0078 lb/1000 lb	.0026 lb/1000 lb
Zinc			.0015 lb/1000 lb	.0005 lb/1000 lb	.0015 lb/1000 lb	.0005 lb/1000 lb
Manganese			.0015 lb/1000 lb	.0005 lb/1000 lb	.0015 lb/1000 lb	.0005 lb/1000 lb
Lead			.00015 lb/1000 lb	.00005 lb/1000 lb	.00015 lb/1000 lb	.00005 lb/1000 lb

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
Part 420 - IRON AND STEEL MANUFACTURING (Continued)			FINAL REGULATIONS, PUBLISHED 6/28/74, EFFECTIVE 6/28/74			
Subpart K - Vacuum Degassing Subcategory (Continued)						
Nitrate			.0141 lb/1000 lb	.0047 lb/1000 lb		
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart L - Continuous Casting Subcategory						
TSS	.0763 lb/1000 lb	.0260 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
Oil & Grease	.0234 lb/1000 lb	.0078 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb	.0156 lb/1000 lb	.0052 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	Daily	*BPT 30 Day	Daily	BAT 30 Day	Daily	New Sources 30 Day
PART 421 - NONFERROUS METALS	FINAL REGULATIONS, PUBLISHED 6/6/74, EFFECTIVE 6/3/74					

Subpart A - Bauxite Refining Subcategory

(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants to navigable waters.

(b) During any calendar month there may be discharged from the overflow of a process waste water impoundment either a volume of process waste water equal to the difference between the precipitation for that month that falls within the impoundment and the evaporation within the impoundment for that month, or, if greater, a volume of process waste water equal to the difference between the mean precipitation for that month that falls within the impoundment and the mean evaporation for that month as established by the National Climatic Center, National Oceanic and Atmospheric Administration, for the area in which such impoundment is located (or as otherwise determined if no monthly data have been established by the National Climatic Center).

Subpart B - Primary Aluminum Smelting Subcategory

Fluoride	2.0 lb/1000 lb of product	1.0 lb/1000 lb of product	0.1 lb/1000 lb of product	0.05 lb/1000 lb of product	0.05 lb/1000 lb of product	0.025 lb/1000 lb of product
TSS	3.0 lb/1000 lb of product	1.5 lb/1000 lb of product	.2 lb/1000 lb of product	.1 lb/1000 lb of product	.1 lb/1000 lb of product	.06 lb/1000 lb of product
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Subpart C - Secondary Aluminum Smelting Subcategory

(a) The following limitations establish the quantity or quality of pollutants or pollutant properties, which may be discharged by a point source subject to the provisions of this subpart and which uses water for metal cooling, after application of the best practicable control technology currently available: There shall be no discharge of process waste water pollutants to navigable waters.

There shall be no discharge of process waste water pollutants to navigable waters.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties which may be discharged by a new source subject to the provisions of this subpart: There shall be no discharge of process waste water pollutants to navigable waters.

(b) Application of the factors listed in section 306(b) of the Act may require variation from the standard of performance set forth in this section for any point source subject

Parameter	*BPT Average of daily values for 30 consecutive days shall not exceed-	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day	
PART 421 - NONFERROUS METALS (Continued)	FINAL REGULATIONS, PUBLISHED 4/8/74, EFFECTIVE 6/3/74					
Subpart C - Secondary Aluminum Smelting Subcategory (Continued)						
	(b) The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart and which uses aluminum fluoride in its magnesium removal process ("demagging process"), after application of the best practicable control technology currently available: There shall be no discharge of process waste water pollutants to navigable waters.					to such standard of performance and which uses chlorine in the magnesium removal process ("demagging" process). If variation is determined to be necessary for any such source, the discharge of process waste water pollutants shall be allowed from the magnesium removal process only, and such source shall be subject to effluent limitations no less stringent than those required by (c), BAT.
	(c) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart and which uses chlorine in its magnesium removal process, after application of the best practicable control technology currently available:					
TSS	175 lbs/1000 lb magnesium removed					
COD	6.5 lbs/1000 lb magnesium removed					
pH	7.5 - 9.0					

Parameter	*BPT Average of daily values for 30 consecutive days shall not exceed -		BAT		New Sources	
		Daily	30 Day	Daily		30 Day

PART 421 - NONFERROUS METALS (Continued) FINAL REGULATIONS, PUBLISHED 4/8/74, EFFECTIVE 6/3/74

Subpart C - Secondary Aluminum Smelting Subcategory (Continued)

(d) The following limitations establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this subpart and which processes residues by wet methods, after application of the best practical control technology currently available.

TSS	1.5 lb/1000 lb of product
Fluoride	.4 lb/1000 lb of product
Ammonia (as N)	.01 lb/1000 lb of product
Aluminum	1.0 lb/1000 lb of product
Copper	.003 lb/1000 lb of product
COD	1.0 lb/1000 lb of product
pH	7.5 - 9.0

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 422 - PHOSPHATE MANUFACTURING	FINAL REGULATIONS, PUBLISHED 2/20/74, EFFECTIVE 4/22/74				(All references to lb/1000 lb are to 1000 lb of product)	
Subpart A - Phosphorus Production Subcategory						
TSS	1.0 lb/1000 lb	0.5 lb/1000 lb	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Total Phosphorus	.30 lb/1000 lb	.15 lb/1000 lb				
Fluoride	.10 lb/1000 lb	.05 lb/1000 lb				
Elemental Phosphorus	No detectable quantity.					
pH	6.0 - 9.0					
Subpart B - Phosphorus Consuming Subcategory						
The provisions of this subpart are applicable to discharges of pollutants resulting from the manufacture of phosphoric acid, phosphorus pentoxide, phosphorus pentasulfide, phosphorus trichloride, and phosphorus oxychloride directly from elemental phosphorus. The production of phosphorus trichloride and phosphorus oxychloride creates waste water pollutants not completely amenable to the procedures utilized for best practicable control technology currently available. The standards set for phosphorus trichloride manufacture and phosphorus oxychloride manufacture, accordingly, must differ from the rest of the subcategory at this level of treatment.						
(a) There shall be no discharge of process waste water pollutants to navigable waters from the manufacture of phosphoric acid, phosphorus pentoxide, or phosphorus pentasulfide.			There shall be no discharge to navigable waters of process waste water pollutants to resulting from the manufacture of phosphoric acid, phosphorus pentoxide, phosphorus pentasulfide, phosphorus trichloride or phosphorus oxychloride.		There shall be no discharge of process waste water pollutants to navigable waters.	
(b) Pollutants or pollutant properties which may be discharged in process waste water from phosphorus trichloride manufacturing on the basis of production:						
TSS	1.4 lb/1000 lb	0.7 lb/1000 lb				
Total Phosphorus	1.6 lb/1000 lb	0.8 lb/1000 lb				
Arsenic	.0001 lb/1000 lb	.00005 lb/1000 lb				
Elemental Phosphorus	No detectable quantity.					
pH	6.0 - 9.0					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 422 - PHOSPHATE MANUFACTURING (Continued)						
Subpart B - Phosphorus Consuming Subcategory (Continued)						
(c) Pollutants or pollutant properties which may be discharged in process waste water from phosphorus oxychloride manufacturing on the basis of production:						
TSS	0.3 lb/1000 lb	0.15 lb/1000 lb				
Total Phosphorus	.34 lb/1000 lb	.17 lb/1000 lb				
pH	6.0 - 9.0					
Subpart C - Phosphate Subcategory						
(a) There shall be no discharge of process waste water pollutants to navigable waters from the manufacture of sodium tripolyphosphate, or animal feed grade calcium phosphate.			There shall be no discharge of process waste water pollutants resulting from the manufacture of sodium tripolyphosphate, animal feed grade calcium phosphate, or human food grade calcium phosphate		There shall be no discharge of process waste water pollutants to navigable waters.	
(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged in process waste water from human food grade calcium phosphate manufacturing based on production:						
TSS	0.12 lb/1000 lb	0.06 lb/1000 lb				
Total Phosphorus	.06 lb/1000 lb	.03 lb/1000 lb				
pH	6.0 - 9.0					

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 423 - STEAM ELECTRIC POWER GENERATING EQUIPMENT - PROPOSED REGULATIONS (FINAL REGULATIONS NOT PROMULGATED AT TIME OF SUMMARY PUBLICATION DATE)						
	(a)(1) There shall be no discharge of heat from a large base-load unit for which construction is completed on or after July 1, 1977, except that heat may be discharged in blowdown from recirculating cooling water systems provided that the temperature at which the blowdown is discharged does not exceed at any time the lowest temperature of the recirculating cooling water prior to the addition of make-up water. (2) The limitation in paragraph (a)(1) of this section shall not apply where the owner or operator of a unit otherwise subject to it can demonstrate: (i) That sufficient land for mechanical draft evaporative cooling towers is not available on the premises or on adjoining property under the ownership or control of the owner or operator, as of the date on which these regulations were proposed, with some amount of land use reassignment and no other available alternative evaporative cooling system is practicable, or (ii) That total dissolved solids concentrations in available intake cooling water exceed 30,000 mg/l, and land not owned or controlled by the owner or operator is located within 150 m (500 ft) downwind (prevailing) of all practicable locations for mechanical draft cooling towers and no other alternative evaporative cooling system is practicable.		(a)(1) There shall be no discharge of heat, except that heat may be discharged in blowdown from the recirculating condenser cooling water system provided that the temperature at which the blowdown is discharged does not exceed at any time the lowest temperature of the recirculating cooling water prior to the addition of make-up water. (2) The limitation set forth in subparagraph (a)(1) shall be achieved as follows: (i) No later than July 1, 1978, by baseload units presently in operation or on which construction is completed prior to July 1, 1977, with a nameplate generating capacity of 500 megawatts or greater. (ii) No later than July 1, 1979, by base-load units presently in operation or on which construction is completed prior to July 1, 1977, with a nameplate generating capacity of less than 500 megawatts, but greater than 299 megawatts. (iii) No later than July 1, 1980, by all other large base-load units. (iv) No later than July 1, 1983, by all other units, including cyclic units, peaking units and small base-load units. (3) The limitation set forth in subparagraph (a)(1) shall not apply to units as to which the owner or operator can demonstrate that (1) sufficient land for mechanical draft		(a) There shall be no discharge of heat by any new sources, except that heat may be discharged in blowdown from recirculating cooling water systems provided that the temperature at which the blowdown is discharged does not exceed at any time the lowest temperature of the recirculating cooling water prior to the addition of make-up water. (b) The effluent limitations in BAT (b) through (n) shall apply to discharges of pollutants other than heat, except as provided in the following: (c) There shall be no discharge of: (1) corrosion inhibitors in blowdown from recirculating cooling water systems; (2) total residual chlorine, or other chemical additives used for biological control in main condenser tubes from nonrecirculating cooling water systems; (3) pollutants from systems providing sluicing of bottom ash from the combustion of oil or fly ash from the combustion of any fuel; or (4) pollutants from nonrecirculating ash sluicing systems. (d) Where waste waters from one source with effluent limitations for a particular pollutant are combined with other waste	

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 423 - STEAM ELECTRIC POWER GENERATING EQUIPMENT (Continued)

(3) The limitations in paragraph (a)(1) shall not apply to discharges from nonrecirculating house service water systems in nuclear-fueled generating units, and to waste water discharges from low-volume waste sources or intermediate volume waste sources other than blowdown from recirculating cooling water systems.

(b) There shall be no discharge of pollutants from clarification water treatment and softening water treatment.

(c) Concentrations of free available chlorine in waste water discharged from nonrecirculating and recirculating cooling water systems shall not exceed average concentrations of 0.2 mg/l and maximum concentrations of 0.5 mg/l at the outlet corresponding to an individual unit during a maximum of one 2-hour period a day. No discharge of tota' residual chlorine is otherwise allowed. No discharge of total residual chlorine is allowed from one unit while another unit at the same plant is being chlorinated. When it can be demonstrated by the owner or operator that higher levels of free available chlorine or more lengthy total periods of application are required to maintain a reasonable level of condenser tube cleanliness for nonrecirculating cooling water systems, discharges of amounts of free available chlorine in excess of the above limitations which are necessary to maintain such level of condenser tube cleanliness may be permitted.

(d) There shall be no discharge of polychlorinated biphenyl transformer fluid.

evaporative cooling towers is not available on the premises, with a reasonably significant amount of land use reassignment or on adjoining properties, whether or not owned or controlled by the owner or operator, and (2) none of the available alternative evaporative cooling systems is practicable.

(4) The limitations set forth in subparagraph (a)(1) shall not apply to discharges from nonrecirculating house service water systems in nuclear-fueled units.

(b) The effluent limitations set forth in BAT (c), (f)(2), (g), (h), (i), (k)(2), and (k)(3) shall apply to discharges of pollutants from recirculating and nonrecirculating cooling water, and sanitary wastes, except that no discharge is allowed of total residual chlorine from recirculating cooling water systems shall that total chromium, total phosphorus (as P), and total zinc in waste water from recirculating cooling water systems shall not exceed daily average amounts, mg, of 0.2 mg/l total chromium x FLOW, total phosphorus (as P) of 5 mg/l x FLOW and 1 mg/l of total zinc x FLOW.

(c)(1) There shall be no discharge of waste water from run-off waste sources, taken collectively as if from one source, unless the first 15 minutes of rainfall run-off are segregated from the remainder during any rainfall event.

waters (such as the combination of waste water from low-volume waste sources with nonrecirculating cooling water), the effluent limitation, mg (or mg/l) for the particular pollutant, excluding pH, for the combined stream shall be the sum of the effluent limitations (for concentration limits apply appropriate dilution factors) for each of the streams which contribute to the combined stream except that the actual amount, mg (or mg/l), of the pollutant in a contributing stream will be used in place of the effluent limitation for those contributing streams where the actual amount, mg (or mg/l), of the pollutant is less than the effluent limitation, mg (or mg/l), for the contributing stream.

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 423 - STEAM ELECTRIC POWER GENERATING EQUIPMENT (Continued)

(e) Total iron and total copper in waste water from low-volume waste sources shall not exceed daily average amounts, mg, of 1 mg/l total copper x FLOW and 1 mg/l total iron x FLOW.

(f)(1) Total suspended solids in waste water from low-volume waste sources shall not exceed daily average amounts, mg. of 15 mg/l x FLOW or a maximum amount, mg, for any one day of 100 mg/l x FLOW.

(2) Total suspended solids in waste water from recirculating cooling water systems shall not exceed daily average amounts, mg, of 15 mg/l x FLOW or a maximum amount, mg, for any one day of 100 mg/l x FLOW.

(3) Total suspended solids in waste water from nonrecirculating ash sluicing systems and from nonrecirculating wet-scrubber air pollution control systems shall not exceed daily average amounts, mg, of 15 mg/l x FLOW or a maximum amount, mg, for any one day of 100 mg/l x FLOW, except that amounts, mg, in excess of the above limitations are allowed only to the extent that the amount, mg, of total suspended solids in waste water from nonrecirculating ash sluicing systems and from nonrecirculating wet-scrubber air pollution control systems does not exceed the amount, mg, of total suspended solids brought into the plant, over the same time span, for use in conjunction with the nonrecirculating ash sluicing system or the nonrecirculating wet-scrubber air pollution control system, respectively.

(2) Total suspended solids and oil and grease in waste waters from the first 15 minutes of rainfall run-off from any rainfall event, taken collectively as if from one source, shall not exceed average concentrations of 15 mg/l and 10 mg/l, respectively, and maximum concentrations of 100 mg/l and 20 mg/l, respectively.

(3) Total suspended solids and oil and grease in waste waters from all but the first 15 munutes of rainfall run-off from any rainfall event, taken collectively as if from one source, shall not exceed average concentrations of 15 mg/l and 10 mg/l, respectively, and maximum concentrations of 100 mg/l and 20 mg/l, respectively.

(d) There shall be no discharge of pollutants other than those controlled by paragraphs (a), (b), and (c) of this section.

(e) There is no effluent limitation on waste waters from the radiological waste system presented in this regulation.

(f) Where waste waters from one source, with effluent limitations for a particular pollutant, are combined with other waste waters (such as the combination of waste water from low-volume waste sources with nonrecirculating cooling water), the effluent limitation, mg (or mg/l), for the particular pollutant, excluding pH, for the combined stream shall be the sum of the effluent limitations (for concentration limits apply appropriate dilution factors) for each of the streams which contribute to the combined stream except that the actual amount, mg (or mg/l), of the pollutant in a contributing

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 423 - STEAM ELECTRIC POWER GENERATING EQUIPMENT (Continued)

(4) Total suspended solids in waste water run-off from rainfall run-off sources, taken collectively as if from one source, including coal pile drainage, yard and roof drainage, and run-off from construction activities shall not exceed average concentrations of 15 mg/l during the time span of each run-off event or a maximum concentration of 100 mg/l at any time.

(g) The pH value of all streams discharged, with the exception of nonrecirculating cooling water, shall be in the range of 6.0 - 9.0 at all times.

(h) Waste waters discharged from the sanitary system shall meet applicable standards for publicly-owned treatment works specified in 40 CFR Part 133.

(i) No debris from the intake means shall be discharged.

(j) There is no effluent limitation on waste waters from the radiological waste system presented in this regulation.

(k)(1) Oil and grease in waste water from low-volume waste sources shall not exceed daily average amounts, mg, of 10 mg/l x FLOW, or a maximum concentration of 20 mg/l at any time.

(2) Oil and grease in waste water from recirculating cooling water systems shall not exceed daily average amounts, mg, of 10 mg/l x FLOW.

stream will be used in place of the effluent limitation for those contributing streams where the actual amount, mg (or mg/l), of the pollutant is less than the effluent limitation, mg (or mg/l), for the contributing stream.

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day

PART 423 - STEAM ELECTRIC POWER GENERATING EQUIPMENT (Continued)

(3) Oil and grease in waste water from rainfall run-off sources, taken collectively as if from one source, shall not exceed daily average concentrations of 10 mg/l during the time span of each run-off event or a maximum concentration of 20 mg/l at any time.

(4) Oil and grease in waste waters from nonrecirculating ash sluicing systems and from nonrecirculating wet-scrubber air pollution control system shall not exceed daily average amounts, mg, of 10 mg/l x FLOW.

(1) Where waste waters from one source with effluent limitations for a particular pollutant are combined with other waste waters (such as the combination of waste water from low-volume sources with non-recirculating cooling water), the effluent limitation, mg (or mg/l), for the particular pollutant, excluding pH, for the combined stream shall be the sum of the effluent limitations (for concentration limits apply appropriate dilution factors) for each of the streams which contribute to the combined stream, except that the actual amount, mg (or mg/l), of the pollutant in a contributing stream will be used in place of the effluent limitation for those contributing streams where the actual amount, mg (or mg/l), of the pollutant is less than the effluent limitation, mg (or mg/l), for the contributing stream.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 424 - FERROALLOY MANUFACTURING	FINAL REGULATIONS, PUBLISHED 2/22/74, EFFECTIVE 4/23/74					
Subpart A - Open Electric Furnaces with Wet Air Pollution Control Devices Subcategory						
TSS	0.703 lb/Mwh	0.352 lb/Mwh	0.052 lb/Mwh	0.026 lb/Mwh	0.052 lb/Mwh	0.026 lb/Mwh
Chromium total	.014 lb/Mwh	.007 lb/Mwh	.0017 lb/Mwh	.0009 lb/Mwh	.0017 lb/Mwh	.0009 lb/Mwh
Chromium VI	.0014 lb/Mwh	.0007 lb/Mwh	.0002 lb/Mwh	.0001 lb/Mwh	.0002 lb/Mwh	.0001 lb/Mwh
Manganese total	.141 lb/Mwh	.070 lb/Mwh	.017 lb/Mwh	.0086 lb/Mwh	.017 lb/Mwh	.0086 lb/Mwh
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Covered Electric Furnaces and Other Smelting Operations with Wet Air Pollution Control Devices Subcategory						
TSS	0.922 lb/Mwh	0.461 lb/Mwh	0.071 lb/Mwh	0.035 lb/Mwh	0.071 lb/Mwh	0.035 lb/Mwh
Chromium total	.018 lb/Mwh	.009 lb/Mwh	.002 lb/Mwh	.0012 lb/Mwh	.002 lb/Mwh	.0012 lb/Mwh
Chromium VI	.0018 lb/Mwh	.0009 lb/Mwh	.0002 lb/Mwh	.0001 lb/Mwh	.0002 lb/Mwh	.0001 lb/Mwh
Manganese total	.184 lb/Mwh	.092 lb/Mwh	.023 lb/Mwh	.012 lb/Mwh	.023 lb/Mwh	.012 lb/Mwh
Cyanide total	.009 lb/Mwh	.005 lb/Mwh	.001 lb/Mwh	.0006 lb/Mwh	.001 lb/Mwh	.0006 lb/Mwh
Phenols	.013 lb/Mwh	.009 lb/Mwh	.0009 lb/Mwh	.0005 lb/Mwh	.0009 lb/Mwh	.0005 lb/Mwh
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Provided, however, that for nonelectric furnace smelting processes, the units of the effluent limitations set forth in this section shall be read as "lb/ton of products," rather than "lb/Mwh," and the limitations (except for pH) shall be three times those listed in the table in this section.

NOTE: "Mwh" shall mean megawatt hour(s) of electrical energy consumed in the smelting process (furnace power consumption).

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 424 - FERROALLOY MANUFACTURING (Continued)			FINAL REGULATIONS, PUBLISHED 2/22/74, EFFECTIVE 4/23/74			
Subpart C - Slag Processing Subcategory						
TSS	5.319 lb/ton processed	2.659 lb/ton processed	0.542 lb/ton processed	0.271 lb/ton processed	0.542 lb/ton processed	0.271 lb/ton processed
Chromium total	.106 lb/ton processed	.053 lb/ton processed	.011 lb/ton processed	.0054 lb/ton processed	.011 lb/ton processed	.0054 lb/ton processed
Manganese total	1.064 lb/ton processed	.532 lb/ton processed	.108 lb/ton processed	.054 lb/ton processed	.108 lb/ton processed	.054 lb/ton processed
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 425 - LEATHER TANNING AND FINISHING	FINAL REGULATIONS, PUBLISHED 4/9/74, EFFECTIVE 6/4/74					
Subpart A - Hair Pulp Unhairing with Chrome Tanning and Finishing Subcategory						
	(a)				(a)	
BOD5	8.0 lb/1000 lb of raw material	4.0 lb/1000 lb of raw material	2.8 lb/1000 lb of raw material	1.40 lb/1000 lb of raw material	8.0 lb/1000 lb of raw material	4.0 lb/1000 lb of raw material
TSS	10.0 lb/1000 lb of raw material	5.0 lb/1000 lb of raw material	3.0 lb/1000 lb of raw material	1.50 lb/1000 lb of raw material	10.0 lb/1000 lb of raw material	5.0 lb/1000 lb of raw material
Chrome	0.20 lb/1000 lb of raw material	0.10 lb/1000 lb of raw material	.1 lb/1000 lb of raw material	.05 lb/1000 lb of raw material	.20 lb/1000 lb of raw material	.10 lb/1000 lb of raw material
Oil & Grease	1.50 lb/1000 lb of raw material	0.75 lb/1000 lb of raw material	1.06 lb/1000 lb of raw material	.53 lb/1000 lb of raw material	1.50 lb/1000 lb of raw material	.75 lb/1000 lb of raw material
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Sulfide			.01 lb/1000 lb of raw material	.005 lb/1000 lb of raw material		
TKN			.54 lb/1000 lb of raw material	.27 lb/1000 lb of raw material		
Fecal Coliform			Maximum at any time: 400 counts per 100 ml.			
	(b)				(b)	
	Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.				Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.	

PART 425 - LEATHER TANNING AND FINISHING (Continued)

FINAL REGULATIONS, PUBLISHED 4/9/74, EFFECTIVE 6/4/74

Subpart B - Hair Save Unhairing with Chrome Tanning and Finishing Subcategory

Parameter	*BPT		BAT		New Sources	
	Daily	30 Day	Daily	30 Day	Daily	30 Day
	(a)				(a)	
BOD5	9.2 lb/1000 lb of raw material	4.6 lb/1000 lb of raw material	3.2 lb/1000 lb of raw material	1.60 lb/1000 lb of raw material	9.2 lb/1000 lb of raw material	4.6 lb/1000 lb of raw material
TSS	11.6 lb/1000 lb of raw material	5.8 lb/1000 lb of raw material	3.6 lb/1000 lb of raw material	1.80 lb/1000 lb of raw material	11.6 lb/1000 lb of raw material	5.8 lb/1000 lb of raw material
Chrome	.24 lb/1000 lb of raw material	.12 lb/1000 lb of raw material	.12 lb/1000 lb of raw material	.06 lb/1000 lb of raw material	.24 lb/1000 lb of raw material	.12 lb/1000 lb of raw material
Oil & Grease	1.80 lb/1000 lb of raw material	.90 lb/1000 lb of raw material	1.26 lb/1000 lb of raw material	.63 lb/1000 lb of raw material	1.80 lb/1000 lb of raw material	.90 lb/1000 lb of raw material
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Sulfide			.012 lb/1000 lb of raw material	.006 lb/1000 lb of raw material		
TKN			.64 lb/1000 lb of raw material	.32 lb/1000 lb of raw material		
Fecal Coliform			Maximum at any time: 400 counts per 100 ml.			

(b)

Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.

(b)

Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 425 - LEATHER TANNING AND FINISHING (Continued)			FINAL REGULATIONS, PUBLISHED 4/9/74, EFFECTIVE 6/4/74			
Subpart C - Unhairing with Vegetable or Alum Tanning and Finishing Subcategory						
	(a)				(a)	
BOD5	7.6 lb/1000 lb of raw material	3.8 lb/1000 lb of raw material	2.6 lb/1000 lb of raw material	1.30 lb/1000 lb of raw material	7.6 lb/1000 lb of raw material	3.8 lb/1000 lb of raw material
TSS	9.6 lb/1000 lb of raw material	4.8 lb/1000 lb of raw material	2.8 lb/1000 lb of raw material	1.40 lb/1000 lb of raw material	9.6 lb/1000 lb of raw material	4.8 lb/1000 lb of raw material
Chrome	.1 lb/1000 lb of raw material	.05 lb/1000 lb of raw material	.1 lb/1000 lb of raw material	.05 lb/1000 lb of raw material	.1 lb/1000 lb of raw material	.05 lb/1000 lb of raw material
Oil & Grease	1.50 lb/1000 lb of raw material	.75 lb/1000 lb of raw material	1.0 lb/1000 lb of raw material	.50 lb/1000 lb of raw material	1.50 lb/1000 lb of raw material	.75 lb/1000 lb of raw material
Sulfide			.01 lb/1000 lb of raw material	.005 lb/1000 lb of raw material		
TKN			.5 lb/1000 lb of raw material	.25 lb/1000 lb of raw material		
Fecal Coliform			Maximum at any time: 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(b)				(b)	
	Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.				Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 425 - LEATHER TANNING AND FINISHING (Continued)			FINAL REGULATIONS, PUBLISHED 4/9/74, EFFECTIVE 6/4/74			
Subpart D - Finishing of Tanned Hides Subcategory						
	(a)				(a)	
BOD5	3.2 lb/1000 lb of raw material	1.6 lb/1000 lb of raw material	1.0 lb/1000 lb of raw material	0.50 lb/1000 lb of raw material	3.2 lb/1000 lb of raw material	1.6 lb/1000 lb of raw material
TSS	4.0 lb/1000 lb of raw material	2.0 lb/1000 lb of raw material	1.2 lb/1000 lb of raw material	.60 lb/1000 lb of raw material	4.0 lb/1000 lb of raw material	2.0 lb/1000 lb of raw material
Chrome	.20 lb/1000 lb of raw material	.10 lb/1000 lb of raw material	.04 lb/1000 lb of raw material	.02 lb/1000 lb of raw material	.20 lb/1000 lb of raw material	.10 lb/1000 lb of raw material
Oil & Grease	.50 lb/1000 lb of raw material	.25 lb/1000 lb of raw material	.48 lb/1000 lb of raw material	.24 lb/1000 lb of raw material	.50 lb/1000 lb of raw material	.25 lb/1000 lb of raw material
Sulfide			.004 lb/1000 lb of raw material	.002 lb/1000 lb of raw material		
TKN			.2 lb/1000 lb of raw material	.10 lb/1000 lb of raw material		
Fecal Coliform			Maximum at any time: 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(b)				(b)	
	Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.				Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 425 - LEATHER TANNING AND FINISHING (Continued)			**FINAL REGULATIONS, PUBLISHED 4/9/74, EFFECTIVE 6/4/74**			
Subpart E - Vegetable or Chrome Tanning of Unhaired Hides Subcategory						
	(a)					
BOD5	9.6 lb/1000 lb of raw material	4.8 lb/1000 lb of raw material	3.2 lb/1000 lb of raw material	1.60 lb/1000 lb of raw material	9.6 lb/1000 lb of raw material	4.8 lb/1000 lb of raw material
TSS	12.0 lb/1000 lb of raw material	6.0 lb/1000 lb of raw material	3.6 lb/1000 lb of raw material	1.80 lb/1000 lb of raw material	12.0 lb/1000 lb of raw material	6.0 lb/1000 lb of raw material
Chrome	.12 lb/1000 lb of raw material	.06 lb/1000 lb of raw material	.12 lb/1000 lb of raw material	.06 lb/1000 lb of raw material	.12 lb/1000 lb of raw material	.06 lb/1000 lb of raw material
Oil & Grease	1.80 lb/1000 lb of raw material	.90 lb/1000 lb of raw material	1.26 lb/1000 lb of raw material	.63 lb/1000 lb of raw material	1.80 lb/1000 lb of raw material	.90 lb/1000 lb of raw material
Sulfide			.012 lb/1000 lb of raw material	.006 lb/1000 lb of raw material		
TKN			.62 lb/1000 lb of raw material	.31 lb/1000 lb of raw material		
Fecal Coliform			Maximum at any time: 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(b)				(b)	
	Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.				Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 425 - LEATHER TANNING AND FINISHING (Continued)			FINAL REGULATIONS, PUBLISHED 4/9/74, EFFECTIVE 6/4/74			
Subpart F - Unhairing with Chrome Tanning and No Finishing Subcategory						
	(a)					
BOD5	5.6 lb/1000 lb of raw material	2.8 lb/1000 lb of raw material	1.4 lb/1000 lb of raw material	0.70 lb/1000 lb of raw material	5.6 lb/1000 lb of raw material	2.8 lb/1000 lb of raw material
TSS	6.8 lb/1000 lb of raw material	3.4 lb/1000 lb of raw material	1.6 lb/1000 lb of raw material	.80 lb/1000 lb of raw material	6.8 lb/1000 lb of raw material	3.4 lb/1000 lb of raw material
Chrome	.20 lb/1000 lb of raw material	.10 lb/1000 lb of raw material	.06 lb/1000 lb of raw material	.03 lb/1000 lb of raw material	.20 lb/1000 lb of raw material	.10 lb/1000 lb of raw material
Oil & Grease	.70 lb/1000 lb of raw material	.35 lb/1000 lb of raw material	.68 lb/1000 lb of raw material	.34 lb/1000 lb of raw material	.70 lb/1000 lb of raw material	.35 lb/1000 lb of raw material
Sulfide			.006 lb/1000 lb of raw material	.003 lb/1000 lb of raw material		
TKN			.28 lb/1000 lb of raw material	.14 lb/1000 lb of raw material		
Fecal Coliform			Maximum at any time: 400 counts per 100 ml.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
	(b)				(b)	
	Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.				Additional allocations equal to one-half the above effluent limitations for BOD5 and TSS established in (a) of this section are allowed any point source subject to such effluent limitations with a production less than 17,000 kg hides per day.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 426 - GLASS MANUFACTURING	SUBPART A - INSULATION FIBERGLASS - FINAL REGULATIONS PUBLISHED 1/22/74, EFFECTIVE 3/25/74 SUBPARTS B - G - FINAL REGULATIONS PUBLISHED 2/14/74, EFFECTIVE 4/15/74 (All references to lb/1000 lb, lb/ton, lb/1000 sq ft, are to units of product)					
Subpart A - Insulation Fiberglass Subcategory						
	(a) There shall be no discharge of process waste water pollutants to navigable waters, except as permitted in subparagraph (b) below.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
	(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged in process waste water from advanced air emission control devices, when such water cannot be consumed in the process.					
Phenol	0.0006 lb/1000 lb		0.0003 lb/1000 lb			
COD	.33 lb/1000 lb		.165 lb/1000 lb			
BOD5	.024 lb/1000 lb		.012 lb/1000 lb			
TSS	.03 lb/1000 lb		.015 lb/1000 lb			
pH	6.0 - 9.0					
Subpart B - Sheet Glass Manufacturing Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 426 - GLASS MANUFACTURING (Continued)						
Subpart C - Rolled Glass Manufacturing Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart D - Plate Glass Manufacturing Subcategory						
TSS	5.52 lb/ton	2.76 lb/ton	0.090 lb/ton	0.090 lb/ton	There shall be no discharge of process waste water pollutants to navigable waters.	
pH	6.0 - 9.0		6.0 - 9.0			
Subpart E - Float Glass Manufacturing Subcategory						
TSS	0.0040 lb/ton	0.0040 lb/ton	0.0014 lb/ton	0.0014 lb/ton	0.0014 lb/ton	0.0014 lb/ton
Oil	.0028 lb/ton	.0028 lb/ton	.0028 lb/ton	.0028 lb/ton	.0028 lb/ton	.0028 lb/ton
Phosphorus	.0001 lb/ton	.0001 lb/ton	.0001 lb/ton	.0001 lb/ton	.0001 lb/ton	.0001 lb/ton
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart F - Automotive Glass Tempering Subcategory						
TSS	0.40 lb/1000 sq ft	0.25 lb/1000 sq ft	0.05 lb/1000 sq ft	0.05 lb/1000 sq ft	0.05 lb/1000 sq ft	0.05 lb/1000 sq ft
Oil	.13 lb/1000 sq ft	.13 lb/1000 sq ft	.10 lb/1000 sq ft	.10 lb/1000 sq ft	.10 lb/1000 sq ft	.10 lb/1000 sq ft
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 426 - GLASS MANUFACTURING (Continued)						
Subpart G - Automotive Glass Laminating Subcategory						
TSS	0.90 lb/1000 sq ft	0.90 lb/1000 sq ft	0.18 lb/1000 sq ft	0.18 lb/1000 sq ft	0.18 lb/1000 sq ft	0.18 lb/1000 sq ft
Oil	.36 lb/1000 sq ft	.36 lb/1000 sq ft	.36 lb/1000 sq ft	.36 lb/1000 sq ft	.36 lb/1000 sq ft	.36 lb/1000 sq ft
Phosphorus	.22 lb/1000 sq ft	.22 lb/1000 sq ft	.06 lb/1000 sq ft	.06 lb/1000 sq ft	.06 lb/1000 sq ft	.06 lb/1000 sq ft
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 427 - ASBESTOS MANUFACTURING	**FINAL REGULATIONS, PUBLISHED 2/26/74, EFFECTIVE 4/29/74**					
Subpart A - Asbestos-Cement Pipe Subcategory						
TSS	1.14 lb/ton of product	0.38 lb/ton of product	There shall be no discharge of process waste water pollutants to navigable waters.		1.14 lb/ton of product	0.38 lb/ton of product
pH	6.0 - 9.0				6.0 - 9.0	
Subpart B - Asbestos-Cement Sheet Subcategory						
TSS	1.35 lb/ton of product	0.45 lb/ton of product	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
pH	6.0 - 9.0					
Subpart C - Asbestos Paper (Starch Binder) Subcategory						
TSS	1.10 lb/ton of product	0.70 lb/ton of product	There shall be no discharge of process water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
pH	6.0 - 9.0					
Subpart D - Asbestos Paper (Elastomeric Binder) Subcategory						
TSS	1.10 lb/ton of product	0.70 lb/ton of product	There shall be no discharge of process waste water pollutants to navigable waters.		1.10 lb/ton of product	0.70 lb/ton of product
pH	6.0 - 9.0				6.0 - 9.0	
Subpart E - Asbestos Millboard Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart F - Asbestos Roofing Subcategory						
COD	0.029 lb/ton of product	0.016 lb/ton of product	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
TSS	.020 lb/ton of product	.012 lb/ton of product				
pH	6.0 - 9.0					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 427 - ASBESTOS MANUFACTURING (Continued)			FINAL REGULATIONS, PUBLISHED 2/26/74, EFFECTIVE 4/29/74			
Subpart G - Asbestos Floor Tile Subcategory						
COD	0.30 lb/mpc of product	0.18 lb/mpc of product	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
TSS	.13 lb/mpc of product	.08 lb/mpc of product				
pH	6.0 - 9.0					

NOTE: "mpc" shall mean 1000 pieces of floor tile. "Pieces" shall mean floor tile measured in the standard size of 12" x 12" x 3/32".

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 428 - RUBBER PROCESSING	FINAL REGULATIONS, PUBLISHED 2/21/74, EFFECTIVE 4/22/74				(All references to lb/1000 lb are to 1000 lb of product)	
Subpart A - Tire and Inner Tube Plants Subcategory						
TSS	0.096 lb/1000 lb	0.064 lb/1000 lb	0.096 lb/1000 lb	0.064 lb/1000 lb	0.096 lb/1000 lb	0.064 lb/1000 lb
Oil&Grease	.024 lb/1000 lb	.016 lb/1000 lb	.024 lb/1000 lb	.016 lb/1000 lb	.024 lb/1000 lb	.016 lb/1000 lb
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Emulsion Crumb Rubber Subcategory						
COD	12.00 lb/1000 lb	8.00 lb/1000 lb	3.12 lb/1000 lb	2.08 lb/1000 lb	Limitations shall be as specified in BPT	
BOD5	.60 lb/1000 lb	.40 lb/1000 lb	.12 lb/1000 lb	.08 lb/1000 lb		
TSS	.98 lb/1000 lb	.65 lb/1000 lb	.24 lb/1000 lb	.16 lb/1000 lb		
Oil&Grease	.24 lb/1000 lb	.16 lb/1000 lb	.12 lb/1000 lb	.08 lb/1000 lb		
pH	6.0 - 9.0		6.0 - 9.0			
Subpart C - Solution Crumb Rubber Subcategory						
COD	5.91 lb/1000 lb	3.94 lb/1000 lb	3.12 lb/1000 lb	2.08 lb/1000 lb	Limitations shall be as specified in BPT	
BOD5	.60 lb/1000 lb	.40 lb/1000 lb	.12 lb/1000 lb	.08 lb/1000 lb		
TSS	.98 lb/1000 lb	.65 lb/1000 lb	.24 lb/1000 lb	.16 lb/1000 lb		
Oil&Grease	.24 lb/1000 lb	.16 lb/1000 lb	.12 lb/1000 lb	.08 lb/1000 lb		
pH	6.0 - 9.0		6.0 - 9.0			

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 428 - RUBBER PROCESSING (Continued)			FINAL REGULATIONS, PUBLISHED 2/21/74, EFFECTIVE 4/22/74			
Subpart D - Latex Rubber Subcategory						
COD	10.27 lb/1000 lb	6.85 lb/1000 lb	2.66 lb/1000 lb	1.78 lb/1000 lb	Limitations shall be as specified in BPT	
BOD5	.51 lb/1000 lb	.34 lb/1000 lb	.11 lb/1000 lb	.07 lb/1000 lb		
TSS	.82 lb/1000 lb	.55 lb/1000 lb	.21 lb/1000 lb	.14 lb/1000 lb		
Oil&Grease	.21 lb/1000 lb	.14 lb/1000 lb	.11 lb/1000 lb	.07 lb/1000 lb		
pH	6.0 - 9.0		6.0 - 9.0			

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 429 - TIMBER PRODUCTS	**FINAL REGULATIONS, PUBLISHED 4/18/74, EFFECTIVE 5/23/74**					
Subpart A - Barking Subcategory						
	(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants into navigable waters.		There shall be no discharge of process waste water pollutants into navigable waters.		(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process waste water pollutants into navigable waters.	
	(b) The following limitations constitute the maximum permissible discharge for those barking processes which utilize hydraulic barkers:				(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this paragraph, which may be discharged by a new source which utilizes a hydraulic barker(s) subject to the provisions of this subpart.	
BOD5	0.09 lb/cu ft of product	0.03 lb/cu ft of product			0.09 lb/cu ft of product	0.03 lb/cu ft of product
TSS	.431 lb/cu ft of product	0.144 lb/cu ft of product			0.431 lb/cu ft of product	0.144 lb/cu ft of product
pH	6.0 - 9.0				6.0 - 9.0	
Subpart B - Veneer Subcategory						
	(a) Subject to the provisions of paragraphs (b), and (c) of this section, there shall be no discharge of process waste water pollutants into navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
	(b) The following limitations constitute the maximum permissible discharge for softwood veneer manufacturing processes which use direct steaming for the conditioning of logs:					

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 429 - TIMBER PRODUCTS (Continued)						
Subpart B - Veneer Subcategory (Continued)						
BOD5	0.045 lb/cu ft of product	0.015 lb/cu ft of product				
pH	6.0 - 9.0					
(c) The following limitations constitute the maximum permissible discharge for hardwood veneer manufacturing processes which use direct steaming for the conditioning of logs:						
BOD5	0.10 lb/cu ft of product	0.034 lb/cu ft of product				
pH	6.0 - 9.0					
Subpart C - Plywood Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters	
Subpart D - Hardboard-Dry Process Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart E - Hardboard-Wet Process Subcategory						
BOD5	15.6 lb/2000 lb of product	5.2 lb/2000 lb of product	5.4 lb/2000 lb of product	1.8 lb/2000 lb of product	5.4 lb/2000 lb of product	1.8 lb/2000 lb of product
TSS	33.0 lb/2000 lb of product	11.0 lb/2000 lb of product	6.6 lb/2000 lb of product	2.2 lb/2000 lb of product	6.6 lb/2000 lb of product	2.2 lb/2000 lb of product
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 429 - TIMBER PRODUCTS (Continued)						
Subpart F - Wood Preserving Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	
Subpart G - Wood Preserving-Steam Subcategory						
COD	68.5 lb/1000 ft^3 of product	34.5 lb/1000 ft^3 of product	13.7 lb/1000 ft^3 of product	6.9 lb/1000 ft^3 of product	13.7 lb/1000 ft^3 of product	6.9 lb/1000 ft^3 of product
Phenols	.14 lb/1000 ft^3 of product	.04 lb/1000 ft^3 of product	.014 lb/1000 ft^3 of product	.004 lb/1000 ft^3 of product	.014 lb/1000 ft^3 of product	.004 lb/1000 ft^3 of product
Oil & Grease	1.5 lb/1000 ft^3 of product	.75 lb/1000 ft^3 of product	.42 lb/1000 ft^3 of product	.21 lb/1000 ft^3 of product	.42 lb/1000 ft^3 of product	.21 lb/1000 ft^3 of product
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart H - Wood Preserving-Boultonizing Subcategory						
	There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.		There shall be no discharge of process waste water pollutants to navigable waters.	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 430 - PULP, PAPER AND PAPERBOARD	FINAL REGULATIONS, PUBLISHED 5/29/74, EFFECTIVE 5/29/74 (All references to lb/ton are lb/ton of product)					
Subpart A - Unbleached Kraft Subcategory						
BOD5	11.2 lb/ton	5.6 lb/ton	5.4 lb/ton	2.7 lb/ton	6.2 lb/ton	3.1 lb/ton
TSS	24.0 lb/ton	12.0 lb/ton	7.4 lb/ton	3.7 lb/ton	15.0 lb/ton	7.5 lb/ton
Color			30.0 lb/ton	20.0 lb/ton	30.0 lb/ton	20.0 lb/ton
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart B - Sodium Based Neutral Sulfite Semi-Chemical Subcategory						
BOD5	17.4 lb/ton	8.7 lb/ton	9.0 lb/ton	4.5 lb/ton	10.4 lb/ton	5.2 lb/ton
TSS	22.0 lb/ton	11.0 lb/ton	10.0 lb/ton	5.0 lb/ton	15.4 lb/ton	7.7 lb/ton
Color			75 percent removal.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart C - Ammonia Base Neutral Sulfite Semi-Chemical Subcategory						
BOD5	16.0 lb/ton	8.0 lb/ton	12.8 lb/ton	6.4 lb/ton	15.0 lb/ton	7.5 lb/ton
TSS	20.0 lb/ton	10.0 lb/ton	10.4 lb/ton	5.2 lb/ton	15.0 lb/ton	7.5 lb/ton
Color			75 percent removal.			
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 430 - PULP, PAPER AND PAPERBOARD (Continued)						
Subpart D - Unbleached Kraft--Neutral Sulfite Semi-Chemical (Cross Recovery) Subcategory						
BOD5	16.0 lb/ton	8.0 lb/ton	6.4 lb/ton	3.2 lb/ton	7.6 lb/ton	3.8 lb/ton
TSS	25.0 lb/ton	12.5 lb/ton	8.4 lb/ton	4.2 lb/ton	16.0 lb/ton	8.0 lb/ton
Color			37.5 lb/ton	25.0 lb/ton	37.5 lb/ton	25.0 lb/ton
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	
Subpart E - Paperboard From Waste Paper Subcategory						
BOD5	6.0 lb/ton	3.0 lb/ton	2.6 lb/ton	1.3 lb/ton	3.0 lb/ton	1.5 lb/ton
TSS	10.0 lb/ton	5.0 lb/ton	3.2 lb/ton	1.6 lb/ton	8.0 lb/ton	4.0 lb/ton
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 431 - BUILDERS PAPER AND BOARD	FINAL REGULATIONS, PUBLISHED 5/9/74, EFFECTIVE 5/9/74					
Subpart A - Builders Paper and Roofing Felt Subcategory						
BOD5	10.0 lb/ton of product	6.0 lb/ton of product	3.5 lb/ton of product	2.0 lb/ton of product	3.5 lb/ton of product	2.0 lb/ton of product
TSS	10.0 lb/ton of product	6.0 lb/ton of product	3.5 lb/ton of product	2.0 lb/ton of product	3.5 lb/ton of product	2.0 lb/ton of product
Settleable Solids	Not to exceed 0.2 ml/l		Not to exceed 0.2 ml/l		Not to exceed 0.2 ml/l	
pH	6.0 - 9.0		6.0 - 9.0		6.0 - 9.0	

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 432 - MEAT PRODUCTS	**FINAL REGULATIONS, PUBLISHED 2/28/74, EFFECTIVE 4/29/74**					
Subpart A - Simple Slaughterhouse Subcategory						
(a) On-site slaughter or subsequent meat, meat product or by-product processing of carcasses of animals slaughtered on-site:						
BOD5	0.24 lb/1000 lb LWK	0.12 lb/1000 lb LWK	0.06 lb/1000 lb LWK	0.03 lb/1000 lb LWK	Limitations shall be as in appropriate BPT with exception that in addition to the pollutants or pollutant properties controlled by that subsection, discharges of ammonia shall not exceed limitations set forth below:	
TSS	.40 lb/1000 lb LWK	.20 lb/1000 lb LWK	.10 lb/1000 lb LWK	.05 lb/1000 lb LWK		
Oil&Grease	.12 lb/1000 lb LWK	.06 lb/1000 lb LWK	10.0 mg/l effluent	--		
Fecal Coliform	400 mpn/100 ml max. at any time		400 mpn/100 max. at any time			
pH	6.0 - 9.0		6.0 - 9.0			
Ammonia			8.0 mg/l effluent	4.0 mg/l effluent	0.34 lb/1000 lb LWK	0.17 lb/1000 lb LWK
(b) If plants process hides from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK				
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK				
(c) If plants process blood from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.014 lb/1000 lb ELWK	0.007 lb/1000 lb ELWK		
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.026 lb/1000 lb ELWK	.013 lb/1000 lb ELWK		
Ammonia					0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK

NOTE: "LWK" (live weight killed) shall mean the total weight of the total number of animals slaughtered during the time to which the effluent limitations apply; i.e., during any one day or any period of thirty consecutive days.

"ELWK" (equivalent live weight killed) shall mean the total weight of the total number of animals slaughtered at locations other than the slaughterhouse or packinghouse, which animals provide hides, blood, viscera or renderable materials for processing at that slaughterhouse, in addition to those derived from animals slaughtered on site.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 432 - MEAT PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 2/28/74, EFFECTIVE 4/29/74					
Subpart A - Simple Slaughterhouse Subcategory						
(d) If plants employ wet or low-temperature rendering of material from plants in addition to its own, add to (a):						
BOD5	0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK		
TSS	.12 lb/1000 lb ELWK	.06 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK		
Ammonia					0.10 lb/1000 lb ELWK	0.05 lb/1000 lb ELWK
(e) If plants employ dry rendering of material from other plants in addition to its own, add to (a):						
BOD5	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK	0.006 lb/1000 lb ELWK	0.003 lb/1000 lb ELWK		
TSS	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK	.014 lb/1000 lb ELWK	.007 lb/1000 lb ELWK		
pH	6.0 - 9.0					
Ammonia					0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK
Subpart B - Complex Slaughterhouse Subcategory						
(a) On-site slaughter or subsequent meat, meat product or by-product processing of carcasses of animals slaughtered on-site:						
BOD5	0.42 lb/1000 lb LWK	0.21 lb/1000 lb LWK	0.08 lb/1000 lb LWK	0.04 lb/1000 lb LWK	The limitations shall be as in appropriate BPT with the following addition:	
TSS	.50 lb/1000 lb LWK	.25 lb/1000 lb LWK	.14 lb/1000 lb LWK	.07 lb/1000 lb LWK		
Oil&Grease	.16 lb/1000 lb LWK	.08 lb/1000 lb LWK	10.0 mg/l effluent	---		
Fecal Coliform	Max. at any time 400 mpn/100 ml		Max. at any time 400 mpn/100 ml			
pH	6.0 - 9.0		6.0 - 9.0			
Ammonia			8.0 mg/l effluent	4.0 mg/l effluent	0.48 lb/1000 lb LWK	0.24 lb/1000 lb LWK

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 432 - MEAT PRODUCTS (Continued)	**FINAL REGULATIONS, PUBLISHED 2/28/74, EFFECTIVE 4/29/74**					
Subpart B - Complex Slaughterhouse Subcategory						
(b) If plants process hides from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK				
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK				
(c) If plants process blood from other plants in addition to its own, add to (a):						
BOD5	**0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.014 lb/1000 lb ELWK	0.007 lb/1000 lb ELWK		
TSS	**0.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.026 lb/1000 lb ELWK	.013 lb/1000 lb ELWK		
Ammonia					0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK
(d) If plants employ wet or low-temperature rendering of material from plants in addition to its own, add to (a):						
BOD5	0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK		
TSS	.12 lb/1000 lb ELWK	.06 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK		
Ammonia					0.10 lb/1000 lb ELWK	0.05 lb/1000 lb ELWK
(e) If plants employ dry rendering of material from other plants in addition to its own, add to (a):						
BOD5	.0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK	0.006 lb/1000 lb ELWK	0.003 lb/1000 lb ELWK		
TSS	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK	.014 lb/1000 lb ELWK	.007 lb/1000 lb ELWK		
Ammonia					0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK

**Corrected per 39 FR 26423, July 19, 1974.

Parameter	BPT Daily	BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 432 - MEAT PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 2/28/74, EFFECTIVE 4/29/74					
Subpart C - Low-Processing Packinghouse Subcategory						
(a) On-site slaughter or subsequent meat, meat product or by-product processing of carcasses of animals slaughtered on-site:						
BOD5	0.34 lb/1000 lb LWK	0.17 lb/1000 lb LWK	0.08 lb/1000 lb LWK	0.04 lb/1000 lb LWK	The limitations shall be as in appropriate BPT, with the following addition:	
TSS	.48 lb/1000 lb LWK	.24 lb/1000 lb LWK	.12 lb/1000 lb LWK	.06 lb/1000 lb LWK		
Oil&Grease	.16 lb/1000 lb LWK	.08 lb/1000 lb LWK	10.0 mg/l effluent	---		
Fecal Coliform	Max. at any time 400 mpn/100 ml		Max. at any time 400 mpn/100 ml			
pH	6.0 - 9.0		6.0 - 9.0			
Ammonia			8.0 mg/l effluent	4.0 mg/l effluent	0.48 lb/1000 lb LWK	0.24 lb/1000 lb LWK
(b) If plants process hides from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK				
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK				
(c) If plants process blood from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.014 lb/1000 lb ELWK	0.007 lb/1000 lb ELWK		
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.026 lb/1000 lb ELWK	.013 lb/1000 lb ELWK		
Ammonia					0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK
(d) If plants employ wet or low-temperature rendering of material from plants in addition to its own, add to (a):						
BOD5	0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK		
TSS	.12 lb/1000 lb ELWK	.06 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK		
Ammonia					0.10 lb/1000 lb ELWK	0.05 lb/1000 lb ELWK

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 432 - MEAT PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 2/28/74, EFFECTIVE 4/29/74					
(e) If plants employ dry rendering of material from other plants in addition to its own, add to (a):						
BOD5	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK	0.006 lb/1000 lb ELWK	0.003 lb/1000 lb ELWK		
TSS	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK	.014 lb/1000 lb ELWK	.007 lb/1000 lb ELWK		
Ammonia					0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK
Subpart D - High-Processing Packinghouse Subcategory						
(a) On-site slaughter or subsequent meat, meat product or by-product processing of carcasses of animals slaughtered on-site:						
BOD5+	0.48 lb/1000 lb LWK	0.24 lb/1000 lb LWK	0.16 lb/1000 lb LWK	0.08 lb/1000 lb LWK	The limitations shall be as in appropriate BPT, with the following addition:	
TSS+	.62 lb/1000 lb LWK	.31 lb/1000 lb LWK	.20 lb/1000 lb LWK	.10 lb/1000 lb LWK		
Oil&Grease	.26 lb/1000 lb LWK	.13 lb/1000 lb LWK	10.0 mg/l effluent	--		
Fecal Coliform	Max. at any time 400 mpn/100 ml		Max. at any time 400 mpn/100 ml			
pH	6.0 - 9.0		6.0 - 9.0			
Ammonia			8.0 mg/l effluent	4.0 mg/l effluent	0.80 lb/1000 lb LWK	0.40 lb/1000 lb LWK
(b) If plants process hides from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK				
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK				

+The values for BOD5 and suspended solids are for average plants, i.e., plants with a ratio of average weight of processed meat products to average LWK of 0.55. Adjustments can be made for high-processing packinghouses at other ratios according to the following equations:

(BPT:) kg BOD5/1000 kg LWK = 0.21+0.23 (v-0.4)
kg SS/1000 kg LWK = 0.28+0.30 (v-0.4)
where v=kg processed meat products/kg LWK.

(BAT:) kg BOD5/1000 kg LWK = 0.07 + 0.08 (v-0.4)
kg SS/1000 kg LWK = 0.05 + 0.10 (v-0.4)
where v=kg processed meat products/kg LWK.

Parameter	*BPT Daily	*BPT 30 Day	BAT Daily	BAT 30 Day	New Sources Daily	New Sources 30 Day
PART 432 - MEAT PRODUCTS (Continued)	FINAL REGULATIONS, PUBLISHED 2/28/74, EFFECTIVE 4/29/74					
(c) If plants process blood from other plants in addition to its own, add to (a):						
BOD5	0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.014 lb/1000 lb ELWK	0.007 lb/1000 lb ELWK		
TSS	.08 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.026 lb/1000 lb ELWK	.013 lb/1000 lb ELWK		
Ammonia					0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK
(d) If plants employ wet or low-temperature rendering of material from plants in addition to its own, add to (a):						
BOD5	0.06 lb/1000 lb ELWK	0.03 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK		
TSS	.12 lb/1000 lb ELWK	.06 lb/1000 lb ELWK	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK		
Ammonia					0.10 lb/1000 lb ELWK	0.05 lb/1000 lb ELWK
(e) If plants employ dry rendering of material from other plants in addition to its own, add to (a):						
BOD5	0.02 lb/1000 lb ELWK	0.01 lb/1000 lb ELWK	0.006 lb/1000 lb ELWK	0.003 lb/1000 lb ELWK		
TSS	.04 lb/1000 lb ELWK	.02 lb/1000 lb ELWK	.014 lb/1000 lb ELWK	.007 lb/1000 lb ELWK		
Ammonia					0.04 lb/1000 lb ELWK	0.02 lb/1000 lb ELWK